BIRD-X SPIKES SPECIAL ADHESIVE

SECTION 1. IDENTIFICATION

Product name SPIKES SPECIAL ADHESIVE

Product code 6700

Manufacturer or supplier's details

Company name of supplier Bird-X, Inc.

845 N Larch Ave, Suite 2 Address

Elmhurst, IL 60126

Telephone (888) 991-6623

Emergency telephone AAPCC: 1-(800)222-1222

Recommended use of the chemical and restrictions on use

Recommended use : Adhesive, binding agents

SECTION 2. HAZARDS

IDENTIFICATION GHS

Classification

Eye irritation : Category 2A

Skin sensitization Category 1

Specific target organ systemic toxicity - repeated

exposure (Oral)

Category 2 (Blood)

GHS Label element

Hazard pictograms





Signal Word : Warning

: H317 May cause an allergic skin reaction. **Hazard Statements**

H319 Causes serious eye irritation.

H373 May cause damage to organs (Blood) through prolonged

or repeated exposure if swallowed.

Prevention: **Precautionary Statements**

P260 Do not breathe dust/ fume/ gas/ mist/ vapors/ spray.

P264 Wash skin thoroughly after handling.

P272 Contaminated work clothing must not be allowed out of

the workplace.

P280 Wear eye protection/ face protection.

P280 Wear protective gloves.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water. P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy

to do. Continue rinsing.

P314 Get medical advice/ attention if you feel unwell.

P333 + P313 If skin irritation or rash occurs: Get medical advice/

attention.

P337 + P313 If eye irritation persists: Get medical advice/

atten-tion.

P363 Wash contaminated clothing before reuse.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Silicone

Sealant

Hazardous ingredients

Chemical Name	CAS-No.	Concentration (%)
Silicon dioxide	7631-86-9	>= 5 - < 10
Methyltri(ethylmethylketoxime)silane	22984-54-9	>= 1 - < 5
Vinyltri (methylethylketoxime) silane	2224-33-1	>= 1 - < 5
N-(3-(Trimethoxysilyl)propyl)ethylenediamine	1760-24-3	>= 0.1 - < 1
Methyltri(ethylmethylketoxime)silane isomers	Not Assigned	>= 0.1 - < 1
and oligomers		

SECTION 4. FIRST AID MEASURES

General advice : In the case of accident or if you feel unwell, seek medical

ad- vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled : If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact : In case of contact, immediately flush skin with soap and

plenty of water.

Remove contaminated clothing and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact : In case of contact, immediately flush eyes with plenty of

water for at least 15 minutes.

If easy to do, remove contact lens, if worn.

Get medical attention.

If swallowed, DO NOT induce vomiting.

Get medical attention if symptoms occur. Rinse mouth thoroughly with water.

Most important symptoms and effects, both acute and

delayed

: May cause an allergic skin reaction. Causes serious eye irritation.

May cause damage to organs through prolonged or repeated

exposure if swallowed.

Protection of first-aiders : First Aid responders should pay attention to self-

protection, and use the recommended personal protective

equipment when the potential for exposure exists.

Notes to physician : Treat symptomatically and supportively.

SECTION 5. FIRE-FIGHTING MEASURES

Suitable extinguishing media : Water spray

Alcohol-resistant foam

Dry chemical

Carbon dioxide (CO2)

Unsuitable extinguishing

media

: None known.

Specific hazards during fire

fighting

: Exposure to combustion products may be a hazard to health.

Hazardous combustion prod-

ucts

Carbon oxides Silicon oxides Formaldehyde Nitrogen oxides (NOx)

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protec- : Use personal protective equipment. tive equipment and emergency procedures

Follow safe handling advice and personal protective equip-

ment recommendations.

Environmental precautions Discharge into the environment must be avoided.

Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material.

For large spills, provide diking or other appropriate containment to keep material from spreading. If diked material can be pumped, store recovered material in appropriate container. Clean up remaining materials from spill with suitable absor-

bent.

Local or national regulations may apply to releases and dis- posal of this material, as well as those materials and

items

employed in the cleanup of releases. You will need to deter-

mine which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE

CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not get on skin or clothing.

Do not swallow. Do not get in eyes.

Handle in accordance with good industrial hygiene and safety

practice.

Keep away from water. Protect from moisture.

Take care to prevent spills, waste and minimize release to

the environment.

Conditions for safe storage : Keep in properly labeled containers.

Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

Ingredients	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Silicon dioxide	7631-86-9	TWA (Dust)	20 Million particles per cubic foot (Silica)	OSHA Z-3
		TWA (Dust)	80 mg/m3 / %SiO2 (Silica)	OSHA Z-3
		TWA	6 mg/m3 (Silica)	NIOSH REL

Hazardous components without workplace control parameters

Ingredients	CAS-No.
Methyltri(ethylmethylketoxime)	22984-54-9
silane	
Vinyltri (methylethylketoxime)	2224-33-1
silane	
N-(3-	1760-24-3
(Trimethoxysilyl)propyl)ethylen	
ediamine	
Methyltri(ethylmethylketoxime)	Not Assigned
silane isomers and oligomers	

Occupational exposure limits of decomposition products

Ingredients	CAS-No.	Value type (Form of exposure)	Control parame- ters / Permissible concentration	Basis
Ethyl methyl ketoxime	96-29-7	TWA	10 ppm	DCC OEL
	Further information: Skin sensitization			
		TWA	10 ppm	US WEEL

Engineering measures

: Processing may form hazardous compounds (see section 10).

Ensure adequate ventilation, especially in confined areas. Minimize workplace exposure concentrations.

Personal protective equipment

Respiratory protection

 General and local exhaust ventilation is recommended to maintain vapor exposures below recommended limits.
 Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn.
 Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air

supplied respirator if there is any potential for uncontrolled

release, exposure levels are unknown, or any other circumstance where air purifying respirators may not

provide adequate protection.

Hand protection

Material : Impervious gloves

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration specific to place of work. Breakthrough time is not determined for the product. Change gloves often! For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before

breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:

Safety goggles

Skin and body protection : Select appropriate protective clothing based on chemical

resistance data and an assessment of the local exposure

potential.

Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

Hygiene measures : Ensure that eye flushing systems and safety showers

are located close to the working place. When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

These precautions are for room temperature handling. Use at elevated temperature or aerosol/spray applications may re-

quire added precautions.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : paste

Color : colorless

Odor : slight

Odor Threshold : No data available

pH : Not applicable

Melting point/freezing point : No of Initial boiling point and boiling : Not

range

: No data available: Not applicable

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : Not classified as a flammability hazard

Upper explosion limit : No data available

Lower explosion limit : No data available

Vapor pressure : Not applicable

Relative vapor density : No data available

Relative density : 1.04

Solubility(ies)

Water solubility
Partition coefficient: n-

octanol/water

: No data available: No data available

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Molecular weight : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable
Possibility of hazardous reac- : Use at

tions

: Stable under normal conditions.

: Use at elevated temperatures may form highly hazardous

compounds.

Can react with strong oxidizing agents.

Hazardous decomposition products will be formed upon

contact with water or humid air.

Hazardous decomposition products will be formed at elevated

temperatures.

Conditions to avoid : Exposure to moisture.

Incompatible materials : Oxidizing agents

Water

Hazardous decomposition products

Contact with water or hu-

: Ethyl methyl ketoxime

mid air

Thermal decomposition : Formaldehyde

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Skin contact Ingestion Eye contact

Acute toxicity

Not classified based on available information.

Product:

Acute oral toxicity : Acute toxicity estimate: > 5,000 mg/kg

Method: Calculation method

Ingredients:

Silicon dioxide:

Acute oral toxicity : LD50 (Rat): > 3,300 mg/kg

Assessment: The substance or mixture has no acute oral tox-

icity

Remarks: Information taken from reference works and the

literature.

Acute inhalation toxicity : LC50 (Rat): > 2.08 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: Information taken from reference works and the

literature.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Information taken from reference works and the

literature.

Methyltri(ethylmethylketoxime)silane:

Acute oral toxicity : LD50 (Rat): > 2,520 mg/kg

Assessment: The substance or mixture has no acute oral tox-

icity

Remarks: Based on test data

Vinyltri (methylethylketoxime) silane:

Acute oral toxicity : LD50 (Rat): > 2,000 mg/kg

Assessment: The substance or mixture has no acute oral tox-

icity

Remarks: Based on test data

Acute dermal toxicity : LD50 (Rat): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Based on test data

N-(3-(Trimethoxysilyl)propyl)ethylenediamine:

Acute oral toxicity : LD50 (Rat): 2,295 mg/kg

Remarks: Based on test data

Acute inhalation toxicity : LC50 (Rat): > 1.49 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist Remarks: Based on test data

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

Assessment: The substance or mixture has no acute dermal

toxicity

Remarks: Based on test data

Skin corrosion/irritation

Not classified based on available information.

Ingredients:

Silicon dioxide:

Result: No skin irritation

Remarks: Information taken from reference works and the literature.

Methyltri(ethylmethylketoxime)silane:

Species: Rabbit

Result: No skin irritation

Remarks: Based on data from similar materials

N-(3-(Trimethoxysilyl)propyl)ethylenediamine:

Species: Rabbit

Result: Mild skin irritation Remarks: Based on test data

Serious eye damage/eye irritation

Causes serious eye irritation.

Ingredients:

Silicon dioxide:

Result: No eye irritation

Remarks: Information taken from reference works and the literature.

Methyltri(ethylmethylketoxime)silane:

Species: Rabbit

Result: Irritation to eyes, reversing within 7 days

Remarks: Based on test data

Vinyltri (methylethylketoxime) silane:

Species: Rabbit

Result: Irreversible effects on the eye

Remarks: Based on test data

N-(3-(Trimethoxysilyl)propyl)ethylenediamine:

Species: Rabbit

Result: Irreversible effects on the eye

Remarks: Based on test data

Methyltri(ethylmethylketoxime)silane isomers and oligomers:

Species: Rabbit

Result: Irritation to eyes, reversing within 7 days Remarks: Based on data from similar materials

Respiratory or skin sensitization

Skin sensitization: May cause an allergic skin reaction.

Respiratory sensitization: Not classified based on available information.

Ingredients: Silicon dioxide:

Assessment: Does not cause skin sensitization.

Test Type: Skin: test type not specified

Species: Guinea pig

Remarks: No known sensitising effect.

Information taken from reference works and the literature.

Methyltri(ethylmethylketoxime)silane:

Assessment: Probability or evidence of skin sensitization in humans

Test Type: Maximization Test (GPMT)

Species: Guinea pig

Remarks: Based on test data

Vinyltri (methylethylketoxime) silane:

Assessment: Probability or evidence of skin sensitization in humans

Test Type: Maximization Test (GPMT)

Species: Guinea pig

Remarks: Causes sensitization.
Based on data from similar materials

N-(3-(Trimethoxysilyl)propyl)ethylenediamine:

Assessment: Probability or evidence of skin sensitization in humans

Test Type: Maximization Test (GPMT)

Species: Guinea pig

Remarks: Causes sensitization.

Information taken from reference works and the literature.

Methyltri(ethylmethylketoxime)silane isomers and oligomers:

Assessment: Probability or evidence of skin sensitization in humans

Test Type: Maximization Test (GPMT)

Species: Guinea pig

Remarks: Causes sensitization.
Based on data from similar materials

Germ cell mutagenicity

Not classified based on available information.

Ingredients:

Silicon dioxide:

Genotoxicity in vitro : Result: negative

Remarks: Information taken from reference works and the

literature.

Genotoxicity in vivo : Application Route: Ingestion

Result: negative

Remarks: Information taken from reference works and the

literature.

Germ cell mutagenicity -

Assessment

: Animal testing did not show any mutagenic effects.

Methyltri(ethylmethylketoxime)silane:

Genotoxicity in vitro : Test Type: Mutagenicity (in vitro mammalian cytogenetic

test) Result: negative

Remarks: Based on test data

Vinyltri (methylethylketoxime) silane:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay

(AMES) Result: negative Remarks: Based on test data

Genotoxicity in vivo : Test Type: In vivo micronucleus test

Species: Mouse

Application Route: Intraperitoneal injection

Result: negative

Remarks: Based on test data

Germ cell mutagenicity -

Assessment

: Animal testing did not show any mutagenic effects.

Carcinogenicity

Not classified based on available information.

IARC No ingredient of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential carcino-

gen by OSHA.

NTP

No ingredient of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated

carcinogen by NTP.

Reproductive toxicity

Not classified based on available information.

Ingredients:

Methyltri(ethylmethylketoxime)silane:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat, male and female Application Route: Ingestion Symptoms: No effects on fertility. Remarks: Based on test data

Effects on fetal development : Test Type: Combined repeated dose toxicity study with

the reproduction/developmental toxicity screening test

Species: Rat, male and female Application Route: Ingestion

Symptoms: No effects on fetal development.

Remarks: Based on test data

Reproductive toxicity - As-

sessment

: No evidence of adverse effects on sexual function and fertility,

or on development, based on animal experiments.

N-(3-(Trimethoxysilyl)propyl)ethylenediamine:

Effects on fertility : Test Type: Combined repeated dose toxicity study with

the reproduction/developmental toxicity screening test

Application Route: Ingestion Symptoms: No effects on fertility. Remarks: Based on test data

Effects on fetal development : Test Type: Combined repeated dose toxicity study with

the reproduction/developmental toxicity screening test

Application Route: Ingestion

Symptoms: No effects on fetal development.

Remarks: Based on test data

Reproductive toxicity - As-

sessment

: No evidence of adverse effects on sexual function and fertility,

or on development, based on animal experiments.

STOT-single exposure

Not classified based on available information.

STOT-repeated exposure

May cause damage to organs (Blood) through prolonged or repeated exposure if swallowed.

Ingredients:

Methyltri(ethylmethylketoxime)silane:

Routes of exposure: Ingestion

Target Organs: Blood

Assessment: Shown to produce significant health effects in animals at concentrations of >10 to

100 mg/kg bw.

Vinyltri (methylethylketoxime) silane:

Routes of exposure: Ingestion

Target Organs: Blood

Assessment: Shown to produce significant health effects in animals at concentrations of >10 to

100 mg/kg bw.

N-(3-(Trimethoxysilyl)propyl)ethylenediamine:

Routes of exposure: Ingestion

Assessment: No significant health effects observed in animals at concentrations of 100 mg/

kg bw or less.

Methyltri(ethylmethylketoxime)silane isomers and oligomers:

Routes of exposure: Ingestion

Target Organs: Blood

Assessment: Shown to produce significant health effects in animals at concentrations of >10 to

100 mg/kg bw.

Repeated dose toxicity

Ingredients:

Methyltri(ethylmethylketoxime)silane:

Species: Rat

Application Route: Ingestion Target Organs: Blood

Remarks: Based on test data

Vinyltri (methylethylketoxime) silane:

Species: Rat

Application Route: Ingestion Target Organs: Blood

Remarks: Based on data from similar materials

N-(3-(Trimethoxysilyl)propyl)ethylenediamine:

Application Route: Ingestion Remarks: Based on test data

Methyltri(ethylmethylketoxime)silane isomers and oligomers:

Species: Rat

Application Route: Ingestion Target Organs: Blood

Remarks: Based on data from similar materials

Aspiration toxicity

Not classified based on available information.

Further information

Product:

Remarks: During use of the material, small amounts of methylethylketoxime (MEKO) will be re- leased. Rodents exposed to chronic MEKO inhalation throughout their lifetimes showed signifi- cant increases in liver tumor rates.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Ingredients:

Methyltri(ethylmethylketoxime)silane:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): > 120 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 203

Remarks: Based on data from similar materials

Toxicity to daphnia and other

aquatic invertebrates

EC50 (Daphnia magna (Water flea)): > 120 mg/l

Exposure time: 48 h

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae : ErC50 (Selenastrum capricornutum (green algae)): 94 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Remarks: Based on data from similar materials

Ecotoxicology Assessment

Acute aquatic toxicity : This product has no known ecotoxicological effects.

N-(3-(TrimethoxysilyI)propyI)ethylenediamine:

Toxicity to fish : LC50 (Danio rerio (zebra fish)): 597 mg/l

Exposure time: 96 h

Method: Directive 67/548/EEC, Annex V, C.1.

Toxicity to daphnia and other

aquatic invertebrates

: EC50 (Daphnia sp.): 81 mg/l

Exposure time: 48 h

Method: Directive 67/548/EEC, Annex V, C.2.

Toxicity to algae : ErC50 (Selenastrum capricornutum (green algae)): 8.8 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

NOEC (Selenastrum capricornutum (green algae)): 3.1 mg/l

Exposure time: 72 h

Method: OECD Test Guideline 201

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

NOEC (Daphnia sp.): > 1 mg/l

Exposure time: 21 d

Toxicity to bacteria : EC50 (Pseudomonas putida): 67 mg/l

Exposure time: 16 h

Test Type: Growth inhibition Method: DIN 38 412 Part 8

Persistence and degradability

Ingredients:

Methyltri(ethylmethylketoxime)silane:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 14.5 % Exposure time: 21 d

Method: OECD Test Guideline 302B

Remarks: Based on data from similar materials

Vinyltri (methylethylketoxime) silane:

Biodegradability : Result: Not readily biodegradable.

Stability in water : Degradation half life: 1 s

N-(3-(Trimethoxysilyl)propyl)ethylenediamine:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 39 %

Method: OECD Test Guideline 301A

Stability in water : Degradation half life: 0.025 h (24.7 °C) pH: 7

Method: OECD Test Guideline 111

Bioaccumulative potential

Ingredients:

Methyltri(ethylmethylketoxime)silane:

Partition coefficient: n- : log Pow: 11.2

octanol/water

N-(3-(Trimethoxysilyl)propyl)ethylenediamine:

Partition coefficient: n-

octanol/water

: log Pow: -0.3

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Resource Conservation and

Recovery Act (RCRA)

: This product has been evaluated for RCRA characteristics and does not meet the criteria of hazardous waste if discarded

in its purchased form.

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Dispose of as unused product.

Empty containers should be taken to an approved waste han-

SECTION 14. TRANSPORT INFORMATION

International Regulation

UNRTDG

Not regulated as a dangerous good

IATA-DGR

Not regulated as a dangerous good

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

Domestic regulation

49 CFR

Not regulated as a dangerous good

SECTION 15. REGULATORY INFORMATION

EPCRA - Emergency Planning and Community Right-to-Know

CERCLA Reportable Quantity

Ingredients	CAS-No.	Component RQ Calculated product	
_		(lbs)	(lbs)
Methanol	67-56-1	5000	*
Ethylenediamine	107-15-3	5000	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 304 Extremely Hazardous Substances Reportable Quantity

Ingredients	CAS-No.	Component RQ	Calculated product RQ
		(lbs)	(lbs)
Ethylenediamine	107-15-3	5000	*

^{*:} Calculated RQ exceeds reasonably attainable upper limit.

SARA 311/312 Hazards : Acute Health Hazard

Chronic Health Hazard

SARA 302 : No chemicals in this material are subject to the

reporting requirements of SARA Title III, Section 302.

SARA 313 : This material does not contain any chemical components

with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III,

Section 313.

US State Regulations

Pennsylvania Right To Know

Dimethyl siloxane, hydroxy-terminated Silicon dioxide Methyltri(ethylmethylketoxime)silane	70131-67-8 7631-86-9 22984-54-9	70 - 90 % 5 - 10 % 1 - 5 %
New Jersey Right To Know		
Dimethyl siloxane, hydroxy-terminated	70131-67-8	70 - 90 %
Silicon dioxide	7631-86-9	5 - 10 %
Methyltri(ethylmethylketoxime)silane	22984-54-9	1 - 5 %
Vinyltri (methylethylketoxime) silane	2224-33-1	1 - 5 %

California Prop 65 WARNING: This product can expose you to chemicals including

Methanol, which is/are known to the State of California to cause birth defects or other reproductive harm. For more

information go to www.p65warnings.ca.gov.

The ingredients of this product are reported in the following inventories:

NZIoC : All ingredients listed or exempt.

TSCA : All chemical substances in this material are included on or

exempted from listing on the TSCA Inventory of Chemical

Substances.

AICS : All ingredients listed or exempt.

IECSC : All ingredients listed or exempt.

ENCS/ISHL : All components are listed on ENCS/ISHL or exempted from

inventory listing.

KECI : All ingredients listed, exempt or notified.

PICCS : All ingredients listed or exempt.

DSL : All chemical substances in this product comply with the CEPA

1999 and NSNR and are on or exempt from listing on the

Canadian Domestic Substances List (DSL).


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

NFPA:



Special hazard.

HMIS III:

HEALTH	2*
FLAMMABILITY	1
PHYSICAL HAZARD	0

0 = not significant, 1 = Slight,

2 = Moderate, 3 = High 4 = Extreme, * = Chronic

Full text of other abbreviations

DCC OFL : Dow Corning Guide

NIOSH REL : USA. NIOSH Recommended Exposure Limits

: USA. Occupational Exposure Limits (OSHA) - Table Z-3 OSHA Z-3

Min- eral Dusts

US WEEL : USA. Workplace Environmental Exposure Levels

(WEEL) DCC OEL / TWA Time weighted average

NIOSH REL / TWA : Time-weighted average concentration for up to a 10-

hour workday during a 40-hour workweek

OSHA Z-3 / TWA 8-hour time weighted average

: 8-hr TWA US WEEL / TWA

Sources of key data used to compile the Material Safety

Data Sheet

: Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date 06/01/2020

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, un- less specified in the text. Material users should review the information and recommendations

in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.