

Issuing Date: 1-Jun-2008 Revision Date: 27-Mar-2015 SDS Number: 9105

1. Identification of the Substance / Preparation and of the Company / Undertaking

Product identifier

Product Name Krystal Kleer -20 degree Windshield Washer Fluid

Stock Numbers 111205 / 111201 / 1111202 / 111205-4

Other means of identification

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Windshield Wiper Fluid

Uses advised against No information available

Details of the supplier of the safety data sheet

Supplier NameSouth/Win, LtdSupplier Address112 Maxfield Rd.

Greensboro, NC 27405

US

Supplier Phone Number Phone: (800) 648-4393

Fax: (336) 398-5680

Emergency Telephone Number CHEMTREC: (800) 424-9300

2. Hazards Identification

Classification

This chemical is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200)

Acute toxicity - Oral	Category 4
Acute toxicity - Dermal	Category 3
Acute toxicity - Inhalation (Vapors)	Category 3
Acute toxicity - Inhalation (Dusts/Mists)	Category 4
Specific target organ toxicity (single exposure)	Category 1
Flammable liquids	Category 3



Revision Date: 27-Mar-2015 SDS Number: 9105 Issuing Date: 1-Jun-2008

GHS Label elements, including precautionary statements

Emergency Overview

Signal Word

Hazard Statement:

Harmful if swallowed Toxic if contact with skin Toxic if inhaled Causes damage to organs Flammable liquid and vapor

Danger

Appearance Blue Physical State Liquid Odor Mild Alcohol

Precautionary Statements - Prevention

Wash face, hands and any exposed skin thoroughly after handling Do not eat, drink or smoke when using this product Wear protective gloves/protective clothing/eye protection/face protection Use only outdoors or in a well-ventilated area Do not breathe dust/fume/gas/mist/vapors/spray Keep away from heat/sparks/open flames/hot surfaces. - No smoking Keep container tightly closed Ground/bond container and receiving equipment

Use explosion-proof electrical/ ventilating/ lighting/ equipment

Use only non-sparking tools

Take precautionary measures against static discharge

Keep cool

Precautionary Statements - Response

IF exposed: Call a POISON CENTER or doctor/physician

Specific treatment (see supplemental first aid instructions on this label)

Skin

Call a POISON CENTER or doctor/physician if you feel unwell

Wash contaminated clothing before reuse

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower

Inhalation

IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing Call a POISON CENTER or doctor/physician

Ingestion

IF SWALLOWED: Call a POISON CENTER or doctor/physician if you feel unwell Rinse mouth



Issuing Date: 1-Jun-2008 Revision Date: 27-Mar-2015 SDS Number: 9105

Fire

In case of fire: Use CO2, dry chemical, or foam for extinction

Precautionary Statements - Storage

Store locked up

Store in a well-ventilated place. Keep container tightly closed

Precautionary Statements - Disposal

Dispose of contents/container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

Unknown Toxicity

0.1% of the mixture consists of ingredient(s) of unknown toxicity

Other information

PROLONGED OR REPEATED CONTACT MAY DRY SKIN AND CAUSE IRRITATION

Interactions with Other Chemicals

Use of alcoholic beverages may enhance toxic effects.

3. Composition / Information on Ingredients

Chemical Name	CAS No	Weight-%	Trade Secret
Methyl alcohol	67-56-1	30 - 40	*

^{*}The exact percentage (concentration) of composition has been withheld as a trade secret

4. First Aid Measures

First aid measures

General Advice Show this safety data sheet to the doctor in attendance. Immediate medical

attention is required.

Eye Contact Rinse immediately with plenty of water, also under the eyelids, for at least 15

minutes. Keep eye wide open while rinsing. Do not rub affected area. Seek immediate medical attention/advice. Remove contact lenses, if present and

easy to do. Continue rinsing.



Issuing Date: 1-Jun-2008 Revision Date: 27-Mar-2015 SDS Number: 9105

Skin Contact Immediate medical attention is required. Wash off immediately with soap and

plenty of water while removing all contaminated clothes and shoes.

Inhalation Remove to fresh air. If not breathing, give artificial respiration. If breathing is

difficult, (trained personnel should) give oxygen.

Ingestion Do NOT induce vomiting. Rinse mouth immediately and drink plenty of water.

Never give anything by mouth to an unconscious person. Call a physician or

poison control center immediately.

first aider

Self-protection of the Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.

Most important symptoms and effects, both acute and delayed

Most Important Coughing and/ or wheezing. Difficulty in breathing.

Symptoms and Effects

Indication of any immediate medical attention and special treatment needed

Notes to Physician Treat symptomatically.

5. Fire-fighting Measures

Suitable Extinguishing Media

Dry chemical, CO2, water spray or regular foam. Use water spray or fog; do not use straight streams.

Unsuitable extinguishing media

CAUTION: All these products have a very low flash point. Use of water spray when fighting fire may be inefficient.

Specific Hazards Arising from the Chemical

Some may be transported hot.

Uniform Fire Code Flammable Liquid: I-C

Hazardous Combustion Products

Carbon oxides.

Explosion Data

Sensitivity to Mechanical No.

Impact

Sensitivity to Static

Yes.

Discharge



Issuing Date: 1-Jun-2008 Revision Date: 27-Mar-2015 SDS Number: 9105

Protective equipment and precautions for firefighters

Move containers from fire area if you can do it without risk.

6. Accidental Release Measures

Personal precautions, protective equipment and emergency procedures

Personal Precautions Avoid contact with skin, eyes or clothing. Ensure adequate ventilation. Use

personal protective equipment as required. Evacuate personnel to safe areas. Do not breathe vapor or mist. Keep people away from and upwind of spill/leak. See section 8 for more information. ELIMINATE all ignition sources (no smoking, flares, sparks or flames in immediate area). Pay attention to flashback. Take precautionary measures against static discharges. All equipment used when handling the product must be grounded. Do not touch or walk through spilled

material.

Other Information Water spray may reduce vapor; but may not prevent ignition in closed spaces.

Environmental Precautions

Environmental Precautions

Prevent entry into waterways, sewers, basements or confined areas.

Methods and material for containment and cleaning up

Methods for Containment A vapor suppressing foam may be used to reduce vapors. Absorb or cover with dry earth, sand or other non-combustible material and transfer to containers.

Methods for cleaning up Use clean non-sparking tools to collect absorbed material. Dike far ahead of liquid spill

for later disposal. Soak up with inert absorbent material. Pick up and transfer to

properly labeled containers.



Issuing Date: 1-Jun-2008 Revision Date: 27-Mar-2015 SDS Number: 9105

7. Handling and Storage

Precautions for safe handling

Handling

Handle in accordance with good industrial hygiene and safety practice. Avoid contact with skin, eyes or clothing. In case of insufficient ventilation, wear suitable respiratory equipment. Do not eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Do not breathe vapor or mist. Use only with adequate ventilation and in closed systems. Use personal protection equipment. Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Use grounding and bonding connection when transferring this material to prevent static discharge, fire or explosion. Use spark-proof tools and explosion-proof equipment. Keep in an area equipped with sprinklers. Use according to package label instructions.

Conditions for safe storage, including any incompatibilities

Storage

Keep containers tightly closed in a dry, cool and well-ventilated place. Keep out of the reach of children. Protect from moisture. Store away from other materials. Store locked up. Keep away from heat, sparks, flame and other sources of ignition (i.e., pilot lights, electric motors and static electricity). Keep in properly labeled containers. Do not store near combustible materials. Keep in an area equipped with sprinklers. Store in accordance with the particular national regulations. Store in accordance with local regulations.

Incompatible Products

None known based on information supplied.

8. Exposure Controls / Personal Protection

Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	NIOSH IDLH
Methyl alcohol	STEL = 250 ppm	TWA: 200 ppm	IDLH: 6000 ppm
67-56-1	TWA: 200 ppm	TWA: 260 mg/m ³	TWA: 200 ppm
	S*	(vacated) TWA: 200 ppm	TWA: 260 mg/m ³
		(vacated) TWA: 260	STEL: 325 mg/m ³
		mg/m ³	STEL: 250 ppm
		(vacated) STEL: 250 ppm	
		(vacated) STEL: 325	
		mg/m ³	
		(vacated) S*	

ACGIH TLV: American Conference of Governmental Industrial Hygienists - Threshold Limit Value OSHA PEL: Occupational Safety and Health Administration - Permissible Exposure Limits Immediately Dangerous to Life or Health

Other Exposure Guidelines

Vacated limits revoked by the Court of Appeals decision in AFL-CIO v. OSHA, 965 F.2d 962 (11th Cir., 1992) See section 15 for national exposure control parameters



Issuing Date: 1-Jun-2008 Revision Date: 27-Mar-2015 SDS Number: 9105

Appropriate engineering controls

Engineering Measures Showers

Eyewash stations Ventilation systems

Individual protection measures, such as personal protective equipment

Eye/Face Protection None required for consumer use. If splashes are likely to occur:. Wear safety glasses

with side shields (or goggles).

Skin and Body Protection None required for consumer use. Repeated or prolonged contact:. Wear protective

gloves and protective clothing.

Respiratory Protection No protective equipment is needed under normal use conditions. If exposure limits are

exceeded or irritation is experienced, ventilation and evacuation may be required.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice. Do not

eat, drink or smoke when using this product. Take off contaminated clothing and wash before reuse. Avoid contact with skin, eyes or clothing. Wear suitable gloves and eye/face protection. No information available. Regular cleaning of equipment, work area and clothing is recommended. Wash hands before breaks and immediately after handling the product. Do not breathe vapor or mist. Contaminated work clothing should not be allowed out of the workplace.

9. Physical and Chemical Properties

Physical and Chemical Properties

Physical StateLiquidAppearanceLiquidOdorMild Alcohol

Color Blue Odor Threshold No information available

<u>Property</u> <u>Values</u> <u>Remarks Method</u>

pН 8.5 None known Melting / freezing point No data available None known 86 °C / 187 °F Boiling point / boiling range None known Flash Point 29 °C / 85 °F None known **Evaporation Rate** No data available None known Flammability (solid, gas) No data available None known

Flammability Limit in Air
Upper flammability limit
Lower flammability limit
No data available
No data available

Vapor pressureNo data availableNone knownVapor densityNo data availableNone known



Issuing Date: 1-Jun-2008	Revision Date: 27-Mar-2015	SDS Number: 9105

Specific GravityNo data availableNone knownWater SolubilityMiscible in waterNone knownSolubility in other solventsNo data availableNone knownPartition coefficient: n-octanol/waterNo data availableNone knownAutoignition temperatureNo data availableNone known

Decomposition temperature
No data available
None known
No data available

Other Information

Softening PointNo data availableVOC Content (%)No data availableParticle SizeNo data available

Particle Size Distribution

10. Stability and Reactivity

Reactivity

No data available.

Chemical stability

Stable under recommended storage conditions.

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerization does not occur.

Conditions to avoid

Excessive heat. Heat, flames and sparks.

Incompatible materials

None known based on information supplied.

Hazardous Decomposition Products

Carbon oxides.

11. Toxicological Information

Information on likely routes of exposure

Product Information



Issuing Date: 1-Jun-2008 Revision Date: 27-Mar-2015 SDS Number: 9105

Inhalation Specific test data for the substance or mixture is not available. Toxic by inhalation.

(based on components).

Eye Contact Specific test data for the substance or mixture is not available.

Skin Contact Specific test data for the substance or mixture is not available. Toxic in contact

with skin. May be absorbed through the skin in harmful amounts. (based on

components).

Ingestion Specific test data for the substance or mixture is not available. May be harmful if

swallowed. (based on components).

Component Information

Chemical Name	Oral LD50	Dermal LD50	Inhalation LC50
Methyl alcohol 67-56-1	= 5628 mg/kg (Rat)	-	= 83.2 mg/L (Rat) 4 h

Information on toxicological effects

Symptoms Coughing and/ or wheezing. Difficulty in breathing.

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Sensitization No information available.

Mutagenic Effects No information available.

Carcinogenicity Contains no ingredient listed as a carcinogen.

Reproductive Toxicity No information available.

STOT - single exposure Based on classification criteria from the 2012 OSHA Hazard Communication

Standard (29 CFR 1910.1200), this product has been determined to cause systemic target organ toxicity from acute exposure. (STOT SE). If this product is a mixture, the classification is not based on toxicology studies for this product, but is based solely on toxicology studies for ingredients found within this product. Detailed substance and/or ingredient information may be provided in other sections of this SDS. Target organs effects listed in this document may result from a single overexposure to this product. Causes damage to organs if

swallowed. Causes damage to organs in contact with skin.

STOT - repeated

exposure

No information available.

Chronic Toxicity No known effect based on information supplied. Effects from this product caused

by acute exposure may cause permanent damage to target organs and/or may

cause chronic conditions.



Issuing Date: 1-Jun-2008 Revision Date: 27-Mar-2015 SDS Number: 9105

Target Organ Effects Respiratory system. Systemic Toxicity. Central Nervous System (CNS). Eyes.

Gastrointestinal tract (GI). Skin.

Aspiration Hazard No information available.

Numerical measures of toxicity Product Information

The following values are calculated based on chapter 3.1 of the GHS document

 ATEmix (oral)
 323.00 mg/kg

 ATEmix (dermal)
 968.00 mg/kg (ATE)

ATEmix (inhalation-dust/mist) 1.62 mg/l ATEmix (inhalation-vapor) 1.0.00 ATEmix

12. Ecological Information

Ecotoxicity

The environmental impact of this product has not been fully investigated.

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
Methyl alcohol		96h LC50: = 28200 mg/L	EC50 = 39000 mg/L	
67-56-1		(Pimephales promelas) 96h	25 min	
		LC50: > 100 mg/L	EC50 = 40000 mg/L	
		(Pimephales promelas) 96h	15 min	
		LC50: 19500 - 20700 mg/L	EC50 = 43000 mg/L	
		(Oncorhynchus mykiss) 96h	5 min	
		LC50: 18 - 20 mL/L		
		(Oncorhynchus mykiss) 96h		
		LC50: 13500 - 17600 mg/L		
		(Lepomis macrochirus)		

Persistence and Degradability

No information available.

Bioaccumulation

Chemical Name	Log Pow
Methyl alcohol	-0.77
67-56-1	

Other adverse effects

No information available.



Issuing Date: 1-Jun-2008 Revision Date: 27-Mar-2015 SDS Number: 9105

13. Disposal Considerations

Waste treatment methods

Disposal methodsThis material, as supplied, is a hazardous waste according to federal

regulations (40 CFR 261).

Contaminated Packaging Dispose of contents/containers in accordance with local regulations.

US EPA Waste Number D001 U154

Chemical Name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Methyl alcohol		Included in waste stream:		U154
67-56-1		F039		

California Hazardous Waste

Codes

This product contains one or more substances that are listed with the State of California as a hazardous waste.

Chemical Name	California Hazardous Waste
Methyl alcohol	Toxic
67-56-1	Ignitable

14. Transport Information

DOT

Proper Shipping Name CONSUMER COMMODITY

Hazard Class ORM-D

Description CONSUMER COMMODITY, ORM-D

212

Emergency Response 128

Guide Number

TDG

UN-No. UN1993

Proper Shipping Name FLAMMABLE LIQUID, N.O.S.

Hazard Class 3
Packing Group III

Description UN1993, FLAMMABLE LIQUID, N.O.S.(METHYL ALCOHOL), 3, III

MEX

UN-No. UN1993

Proper Shipping Name FLAMMABLE LIQUID, N.O.S.

Hazard Class 3
Packing Group III

Description UN1993 FLAMMABLE LIQUID, N.O.S.(METHYL ALCOHOL), 3, III



Revision Date: 27-Mar-2015 SDS Number: 9105 Issuing Date: 1-Jun-2008

ICAO UN-No.

UN1993

Proper Shipping Name

FLAMMABLE LIQUID, N.O.S.

Hazard Class

Ш

Packing Group Description

UN1993, FLAMMABLE LIQUID, N.O.S.(METHYL ALCOHOL), 3, III

IATA

UN-No.

UN1993

Proper Shipping Name

FLAMMABLE LIQUID, N.O.S.

Hazard Class

Ш

Packing Group Description

UN1993, FLAMMABLE LIQUID, N.O.S.(METHYL ALCOHOL), 3, III

IMDG/IMO

UN-No.

UN1993

Proper Shipping Name

FLAMMABLE LIQUID, N.O.S.

Hazard Class

3 Ш

Packing Group EmS-No.

F-E, S-E

Description

UN1993, FLAMMABLE LIQUID, N.O.S.(METHYL ALCOHOL), 3, III, FP 34C

RID

UN-No.

UN1993

Ш

F1

Proper Shipping Name

FLAMMABLE LIQUID, N.O.S.

Hazard Class Packing Group

Classification code

Description UN1993 FLAMMABLE LIQUID, N.O.S.(METHYL ALCOHOL), 3, III

ADR

UN-No.

UN1993

Proper Shipping Name

FLAMMABLE LIQUID, N.O.S.

Hazard Class Packing Group

Classification code

Ш F1

Description

UN1993 FLAMMABLE LIQUID, N.O.S. (METHYL ALCOHOL), 3, III

<u>ADN</u>

UN-No.

UN1993

Ш

F1

3

Proper Shipping Name

FLAMMABLE LIQUID, N.O.S.

Hazard Class Packing Group Classification code

Special Provisions

274, 601, 640E

Description

UN1993 FLAMMABLE LIQUID, N.O.S. (METHYL ALCOHOL), 3, III

Hazard Labels



Issuing Date: 1-Jun-2008 Revision Date: 27-Mar-2015 SDS Number: 9105

Limited Quantity Ventilation

5 L VE01

15. Regulatory Information

International Inventories

TSCA

Complies

DSL

All components are listed either on the DSL or NDSL.

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains a chemical or chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

Chemical Name	CAS No	Weight-%	SARA 313 - Threshold Values %
Methyl alcohol - 67-56-1	67-56-1	30 - 40	1.0

SARA 311/312 Hazard

<u>Categories</u>

Acute Health Hazard Yes
Chronic Health Hazard Yes
Fire Hazard Yes
Sudden release of pressure hazard No
Reactive Hazard No

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302)

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
Methyl alcohol 67-56-1	5000 lb		RQ= 2270 kg final RQ RQ= 5000 lb final RQ



Issuing Date: 1-Jun-2008 Revision Date: 27-Mar-2015 SDS Number: 9105

US State Regulations

California Proposition 65

This product contains the following Proposition 65 chemicals.

Chemical Name	California Proposition 65
Methyl alcohol - 67-56-1	Developmental

US State Right-to-know Regulations

Chemical Name	New Jersey	Massachusetts	Pennsyl vania	Rhode Island	Illinois
Methyl alcohol 67-56-1	Х	Х	Х	Χ	Х

International Regulations

Mexico

National occupational exposure limits

Component	Carcinogen Status	Exposure Limits
Methyl alcohol		Mexico: TWA= 200 ppm
67-56-1 (15 - 40)		Mexico: TWA= 260 mg/m ³
		Mexico: STEL= 250 ppm
		Mexico: STEL= 310 mg/m ³

Mexico - Occupational Exposure Limits - Carcinogens

Canada

WHMIS Hazard Class

B2 - Flammable liquid D2A - Very toxic materials D2B - Toxic materials



16. Other Information



Issuing Date: 1-Jun-2008 Revision Date: 27-Mar-2015 SDS Number: 9105

NFPA Health Hazards 3 Flammability 3 Instability 0 Physical and Chemical

HMIS Health Hazards 3 * Flammability 3 Physical Hazard 0 Personal Protection X

Prepared By: Randy Boitz

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet