MaxPar[®] G2-60 (50 GAL)

Components/CAS#; Hydrotreated Petroleum Distillate, Light Paraffin C15-30 64742-55-8

..... MADE IN U.S.A.....

BEFORE HANDLING OR USING, READ AND UNDERSTAND THE CURRENT MATERIAL SAFETY DATA SHEET FOR THIS PRODUCT!

Storage: Keep Container(s) tightly closed. Use and store this material in cool, dry, well-ventilated areas away from heat and all sources of ignition. Store only in approved containers. Keep away from any incompatible material. Protect container(s) against physical damage.

Emergency Overview 24 Hour Emergency Telephone Numbers: Spill, Leak, Fire or Accident Call CHEMTREC: North America: (800) 424-9300 Others: (703) 527- 3887 (collect)



DANGER

Aspiration Hazard. May be fatal if swallowed and enters airways.

PRECAUTIONARY STATEMENTS

If swallowed immediately call a poison control center / doctor. Do NOT induce vomiting.

Avoid breathing vapors. If inhaled remove person to fresh air. Wash thoroughly after handling. Store locked up.

Dispose of contents/container to an approved waste disposal site.

FIRST AID

Eye: If irritation or redness develops, move victim away from exposure and into fresh air. Flush eyes with clean water. If symptoms persist, seek medical attention

Skin: Wipe material from skin and remove contaminated shoes and clothing. Cleanse affected area(s) thoroughly by washing with mild soap and water and, if necessary, a waterless skin cleanser. If irritation or redness develops and persists, seek medical attention.

Inhalation (Breathing): If respiratory symptoms develop, move victim away from source of exposure and into fresh air. If symptoms persist, seek medical attention. If victim is not breathing, clear airway and immediately begin artificial respiration. If breathing difficulties develop, oxygen should be administered by qualified personnel. Seek immediate medical attention.

Ingestion (Swallowing): First aid is not normally required; however, if swallowed and symptoms develop, seek medical attention.

Batch Number: RP-1311-1

HMIS RATING

Health:	0
Flammability:	1
Instability:	0

Flash point: > 340 °F / 171°C

50 GALLON NET VOLUME

362 LBS NET WEIGHT 36 LBS TARE WEIGHT 398 LBS GROSS WIEGHT

Attention!

Empty containers retain residue and may be dangerous. Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition

In emergency call: (24 hours) 800-424-9300



1102 Ave R Grand Prairie, TX 75050