according to the OSHA Hazard Communication Standard



## MERIT WP75 4X(4X1.6OZ) CAS US

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 07/26/2023

 2.0
 08/25/2023
 11251929-00002
 Date of first issue: 07/26/2023

#### **SECTION 1. IDENTIFICATION**

Product name : MERIT WP75 4X(4X1.6OZ) CAS US

Product code : Article/SKU: D00000962 UVP: 04399455 Specification:

102000007120

Manufacturer or supplier's details

Company name of supplier : Environmental Science U.S. LLC.

Address : 5000 Centregreen Way, Suite 400

Cary NC 27513

Telephone : 1-800-331-2867

Emergency telephone : +1 703-741-5970

E-mail address : uscontact@envu.com

Recommended use of the chemical and restrictions on use

Recommended use : Insecticide

Restrictions on use : See product label for restrictions.

#### **SECTION 2. HAZARDS IDENTIFICATION**

# GHS classification in accordance with the OSHA Hazard Communication Standard (29 CFR 1910.1200)

Combustible dust

Acute toxicity (Oral) : Category 4

**GHS** label elements

Hazard pictograms



Signal Word : Warning

Hazard Statements : May form combustible dust concentrations in air.

H302 Harmful if swallowed.

Precautionary Statements : Prevention:

P264 Wash skin thoroughly after handling.

P270 Do not eat, drink or smoke when using this product.

Response:

P301 + P312 + P330 IF SWALLOWED: Call a doctor if you feel

according to the OSHA Hazard Communication Standard



## **MERIT WP75 4X(4X1.6OZ) CAS US**

Version SDS Number: Date of last issue: 07/26/2023 Revision Date: 2.0 08/25/2023 11251929-00002 Date of first issue: 07/26/2023

unwell. Rinse mouth.

Disposal:

P501 Dispose of contents and container to an approved waste

disposal plant.

#### Other hazards

Dust contact with the eyes can lead to mechanical irritation.

#### SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture Mixture

Wettable powder (WP) Chemical nature

#### Components

| Chemical name   | CAS-No.     | Concentration (% w/w) |
|---|-------------|-----------------------|
| Imidacloprid  | 138261-41-3 | >= 70 - < 90          |
| Silicic acid, aluminum sodium salt  | 1344-00-9   | >= 10 - < 20          |
| Naphthalenesulfonic acid, bis(1-methylethyl)-, Methyl derivatives, sodium salts | 68909-82-0  | >= 1 - < 5            |

Actual concentration is withheld as a trade secret

#### **SECTION 4. FIRST AID MEASURES**

General advice In the case of accident or if you feel unwell, seek medical ad-

vice immediately.

When symptoms persist or in all cases of doubt seek medical

advice.

If inhaled If inhaled, remove to fresh air.

Get medical attention if symptoms occur.

In case of skin contact In case of contact, immediately flush skin with plenty of water.

Remove contaminated clothing and shoes.

Get medical attention. Wash clothing before reuse.

Thoroughly clean shoes before reuse.

In case of eye contact If in eyes, rinse well with water.

Get medical attention if irritation develops and persists.

If swallowed, DO NOT induce vomiting unless directed to do If swallowed

> so by medical personnel. Get medical attention.

Rinse mouth thoroughly with water.

No symptoms known or expected.

Never give anything by mouth to an unconscious person.

Most important symptoms

and effects, both acute and

Harmful if swallowed.

delayed Dust contact with the eyes can lead to mechanical irritation.

according to the OSHA Hazard Communication Standard



## MERIT WP75 4X(4X1.6OZ) CAS US

Version Revision Date: SDS Number: Date of last issue: 07/26/2023 2.0 08/25/2023 11251929-00002 Date of first issue: 07/26/2023

This product contains a nicotinoid.

Protection of first-aiders : First Aid responders should pay attention to self-protection,

and use the recommended personal protective equipment when the potential for exposure exists (see section 8).

Notes to physician : There is no specific antidote available.

Treat symptomatically.

In case of ingestion gastric lavage should be considered in cases of significant ingestions only within the first 2 hours. However, the application of activated charcoal and sodium

sulphate is always advisable.

Appropriate supportive and symptomatic treatment as indica-

ted by the patient's condition is recommended.

#### **SECTION 5. FIRE-FIGHTING MEASURES**

Suitable extinguishing media : Water spray

Alcohol-resistant foam Carbon dioxide (CO2)

Dry chemical

Unsuitable extinguishing

media

High volume water jet

Specific hazards during fire

fighting

Avoid generating dust; fine dust dispersed in air in sufficient

concentrations, and in the presence of an ignition source is a potential dust explosion hazard.

Do not use a solid water stream as it may scatter and spread

fire

Exposure to combustion products may be a hazard to health.

Hazardous combustion prod-

ucts

Carbon oxides

Nitrogen oxides (NOx) Chlorine compounds

Sulfur oxides Metal oxides Silicon oxides

Specific extinguishing meth-

ods

Use extinguishing measures that are appropriate to local cir-

cumstances and the surrounding environment. Use water spray to cool unopened containers.

Remove undamaged containers from fire area if it is safe to do

SO.

Evacuate area.

Special protective equipment

for fire-fighters

In the event of fire, wear self-contained breathing apparatus.

Use personal protective equipment.

#### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emer-

Use personal protective equipment.

Follow safe handling advice (see section 7) and personal pro-

according to the OSHA Hazard Communication Standard



## MERIT WP75 4X(4X1.6OZ) CAS US

Version Revision Date: SDS Number: Date of last issue: 07/26/2023 2.0 08/25/2023 11251929-00002 Date of first issue: 07/26/2023

gency procedures tective equipment recommendations (see section 8).

Environmental precautions : Avoid release to the environment.

Prevent further leakage or spillage if safe to do so. Retain and dispose of contaminated wash water.

Local authorities should be advised if significant spillages

cannot be contained.

Methods and materials for containment and cleaning up

Sweep up or vacuum up spillage and collect in suitable con-

tainer for disposal.

Avoid dispersal of dust in the air (i.e., clearing dust surfaces

with compressed air).

Dust deposits should not be allowed to accumulate on surfaces, as these may form an explosive mixture if they are relea-

sed into the atmosphere in sufficient concentration.

Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine

which regulations are applicable.

Sections 13 and 15 of this SDS provide information regarding

certain local or national requirements.

#### **SECTION 7. HANDLING AND STORAGE**

Technical measures : Static electricity may accumulate and ignite suspended dust

causing an explosion.

Provide adequate precautions, such as electrical grounding

and bonding, or inert atmospheres.

Local/Total ventilation : Use only with adequate ventilation.

Advice on safe handling : Do not get on skin or clothing.

Do not breathe dust. Do not swallow.

Avoid contact with eyes.

Wash skin thoroughly after handling.

Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure as-

sessment

Minimize dust generation and accumulation. Keep container closed when not in use. Keep away from heat and sources of ignition.

Take precautionary measures against static discharges. Do not eat, drink or smoke when using this product.

Take care to prevent spills, waste and minimize release to the

environment.

Conditions for safe storage : Keep in properly labeled containers.

Store in accordance with the particular national regulations.

Materials to avoid : Do not store with the following product types:

Strong oxidizing agents

according to the OSHA Hazard Communication Standard



## MERIT WP75 4X(4X1.6OZ) CAS US

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 07/26/2023

 2.0
 08/25/2023
 11251929-00002
 Date of first issue: 07/26/2023

#### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Ingredients with workplace control parameters

inert or nuisance dust 50 Million particles per cubic foot

Value type (Form of exposure): TWA (total dust)

Basis: OSHA Z-3

15 mg/m<sup>3</sup>

Value type (Form of exposure): TWA (total dust)

Basis: OSHA Z-3

5 mg/m<sup>3</sup>

Value type (Form of exposure): TWA (respirable fraction)

Basis: OSHA Z-3

15 Million particles per cubic foot

Value type (Form of exposure): TWA (respirable fraction)

Basis: OSHA Z-3

Dust, nuisance dust and par-

ticulates

10 mg/m<sup>3</sup>

Value type (Form of exposure): PEL (Total dust)

Basis: CAL PEL

5 mg/m<sup>3</sup>

Value type (Form of exposure): PEL (respirable dust fraction)

Basis: CAL PEL

| Components                         | CAS-No.   | Value type<br>(Form of<br>exposure) | Control parameters / Permissible concentration | Basis |
|------------------------------------|-----------|-------------------------------------|--|-------|
| Silicic acid, aluminum sodium salt | 1344-00-9 | TWA (Respirable particulate matter) | 1 mg/m³<br>(Aluminum)                          | ACGIH |

**Engineering measures** : Ensure adequate ventilation, especially in confined areas.

Minimize workplace exposure concentrations. Apply measures to prevent dust explosions.

Ensure that dust-handling systems (such as exhaust ducts, dust collectors, vessels, and processing equipment) are designed in a manner to prevent the escape of dust into the work area (i.e., there is no leakage from the equipment).

Personal protective equipment

Respiratory protection : General and local exhaust ventilation is recommended to

according to the OSHA Hazard Communication Standard



## MERIT WP75 4X(4X1.6OZ) CAS US

Version Revisi 2.0 08/25

Revision Date: 08/25/2023

SDS Number: 11251929-00002

Date of last issue: 07/26/2023 Date of first issue: 07/26/2023

maintain vapor exposures below recommended limits. Where concentrations are above recommended limits or are unknown, appropriate respiratory protection should be worn. Follow OSHA respirator regulations (29 CFR 1910.134) and use NIOSH/MSHA approved respirators. Protection provided by air purifying respirators against exposure to any hazardous chemical is limited. Use a positive pressure air supplied respirator if there is any potential for uncontrolled release, exposure levels are unknown, or any other circumstance where air purifying respirators may not provide adequate protection.

Hand protection

Material

: Nitrile rubber

Remarks : Choose gloves to protect hands against chemicals depending

on the concentration specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday. Breakthrough time is not determined for the pro-

duct. Change gloves often!

Eye protection : Wear the following personal protective equipment:

Safety goggles

Skin and body protection : Skin should be washed after contact.

Hygiene measures : If exposure to chemical is likely during typical use, provide

eye flushing systems and safety showers close to the wor-

king place.

When using do not eat, drink or smoke. Wash contaminated clothing before re-use.

#### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : powder

Color : light beige, white

Odor : none

Odor Threshold : No data available

pH : 7

Concentration: 1 %

(aqueous suspension) Distilled water

Melting point/freezing point : No data available

according to the OSHA Hazard Communication Standard



## **MERIT WP75 4X(4X1.6OZ) CAS US**

Version Revision Date: 2.0 08/25/2023

SDS Number: 11251929-00002

Date of last issue: 07/26/2023 Date of first issue: 07/26/2023

Initial boiling point and boiling :

range

No data available

Flash point : Not applicable

Evaporation rate : Not applicable

Flammability (solid, gas) : May form explosive dust-air mixture.

Upper explosion limit / Upper

flammability limit

Not applicable

Lower explosion limit / Lower

flammability limit

Not applicable

Vapor pressure : Not applicable

Relative vapor density : Not applicable

Density : Not applicable

Bulk density : 480.554 kg/m³Tap density

Solubility(ies)

Water solubility : dispersible

Partition coefficient: n-

octanol/water

Not applicable

Autoignition temperature : No data available

Decomposition temperature : No data available

Viscosity

Viscosity, dynamic : Not applicable

Viscosity, kinematic : Not applicable

Explosive properties : Not explosive

Oxidizing properties : The substance or mixture is not classified as oxidizing.

Minimum ignition energy : > 100 - < 300 mJ

Method: ASTM E-2019

Particle size : No data available

### **SECTION 10. STABILITY AND REACTIVITY**

according to the OSHA Hazard Communication Standard



## MERIT WP75 4X(4X1.6OZ) CAS US

Version Revision Date: SDS Number: Date of last issue: 07/26/2023 2.0 08/25/2023 11251929-00002 Date of first issue: 07/26/2023

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reac-

tions

May form explosive dust-air mixture.

Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Avoid dust formation.

Incompatible materials : Oxidizing agents

Hazardous decomposition

products

No hazardous decomposition products are known.

#### **SECTION 11. TOXICOLOGICAL INFORMATION**

#### Information on likely routes of exposure

Inhalation Skin contact Ingestion Eye contact

#### Acute toxicity

Harmful if swallowed.

**Product:** 

Acute oral toxicity : LD50 (Rat): 1,858 mg/kg

#### **Components:**

Imidacloprid:

Acute oral toxicity : LD50 (Mouse, male): 131 mg/kg

Method: OECD Test Guideline 401

Acute inhalation toxicity : LC50 (Rat): > 5.323 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rat): > 5,000 mg/kg

#### Silicic acid, aluminum sodium salt:

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 2.08 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: The substance or mixture has no acute inhala-

tion toxicity

Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg

according to the OSHA Hazard Communication Standard



## **MERIT WP75 4X(4X1.6OZ) CAS US**

Version Revision Date: SDS Number: Date of last issue: 07/26/2023 2.0 08/25/2023 11251929-00002 Date of first issue: 07/26/2023

П

Naphthalenesulfonic acid, bis(1-methylethyl)-, Methyl derivatives, sodium salts:

Acute oral toxicity : LD50 (Rat, female): > 300 - 2,000 mg/kg

Method: OECD Test Guideline 423

Skin corrosion/irritation

Not classified based on available information.

**Components:** 

Imidacloprid:

Species : Rabbit

Result : No skin irritation

Silicic acid, aluminum sodium salt:

Species : Rabbit

Result : No skin irritation

Naphthalenesulfonic acid, bis(1-methylethyl)-, Methyl derivatives, sodium salts:

Species : Rabbit

Method : OECD Test Guideline 404

Result : Skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

**Product:** 

Species : Rabbit

Result : No eye irritation

**Components:** 

Imidacloprid:

Species : Rabbit

Result : No eye irritation

Silicic acid, aluminum sodium salt:

Species : Rabbit

Result : No eye irritation

Naphthalenesulfonic acid, bis(1-methylethyl)-, Methyl derivatives, sodium salts:

Species : Bovine cornea

Method : OECD Test Guideline 437

Result : Irreversible effects on the eye

according to the OSHA Hazard Communication Standard



## **MERIT WP75 4X(4X1.6OZ) CAS US**

Version Revision Date: SDS Number: Date of last issue: 07/26/2023 2.0 08/25/2023 11251929-00002 Date of first issue: 07/26/2023

#### Respiratory or skin sensitization

#### Skin sensitization

Not classified based on available information.

#### Respiratory sensitization

Not classified based on available information.

#### **Components:**

#### Imidacloprid:

Test Type : Magnusson-Kligman-Test

Routes of exposure : Skin contact Species : Guinea pig

Method : OECD Test Guideline 406

Result : negative

#### Naphthalenesulfonic acid, bis(1-methylethyl)-, Methyl derivatives, sodium salts:

Test Type : Direct Peptide Reactivity Assay (DPRA)

Method : OECD Test Guideline 442C

Result : equivocal

Test Type : KeratinoSens assay

Method : OECD Test Guideline 442D

Result : negative

Test Type : Dendritic cell activation test
Method : OECD Test Guideline 442E

Result : negative

Assessment : Does not cause skin sensitization.

### Germ cell mutagenicity

Not classified based on available information.

#### **Components:**

#### Imidacloprid:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Result: negative

Test Type: In vitro mammalian cell gene mutation test

Result: negative

Test Type: Chromosome aberration test in vitro

Result: negative

#### Silicic acid, aluminum sodium salt:

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro

Result: negative

Genotoxicity in vivo : Test Type: Chromosome aberration test in vitro

Species: Rat

according to the OSHA Hazard Communication Standard



## MERIT WP75 4X(4X1.6OZ) CAS US

Version Revision Date: SDS Number: Date of last issue: 07/26/2023 2.0 08/25/2023 11251929-00002 Date of first issue: 07/26/2023

Application Route: Ingestion

Result: negative

#### Naphthalenesulfonic acid, bis(1-methylethyl)-, Methyl derivatives, sodium salts:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)

Method: OECD Test Guideline 471

Result: negative

#### Carcinogenicity

Not classified based on available information.

#### **Components:**

#### Silicic acid, aluminum sodium salt:

Species : Rat

Application Route : Intraperitoneal injection

Exposure time : 3 Years
Result : negative

IARC No ingredient of this product present at levels greater than or equal to 0.1% is

identified as probable, possible or confirmed human carcinogen by IARC.

**OSHA**No component of this product present at levels greater than or equal to 0.1% is

on OSHA's list of regulated carcinogens.

NTP No ingredient of this product present at levels greater than or equal to 0.1% is

identified as a known or anticipated carcinogen by NTP.

### Reproductive toxicity

Not classified based on available information.

### **Components:**

#### Imidacloprid:

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Ingestion

Result: negative

#### Silicic acid, aluminum sodium salt:

Effects on fetal development : Test Type: Embryo-fetal development

Species: Rat

Application Route: Ingestion

Result: negative

#### Naphthalenesulfonic acid, bis(1-methylethyl)-, Methyl derivatives, sodium salts:

Effects on fertility : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

according to the OSHA Hazard Communication Standard



## **MERIT WP75 4X(4X1.6OZ) CAS US**

Version Revision Date: SDS Number: Date of last issue: 07/26/2023 2.0 08/25/2023 11251929-00002 Date of first issue: 07/26/2023

Result: negative

Effects on fetal development : Test Type: Combined repeated dose toxicity study with the

reproduction/developmental toxicity screening test

Species: Rat

Application Route: Ingestion Method: OECD Test Guideline 422

Result: negative

#### STOT-single exposure

Not classified based on available information.

#### STOT-repeated exposure

Not classified based on available information.

#### **Components:**

#### Silicic acid, aluminum sodium salt:

Routes of exposure : inhalation (dust/mist/fume)

Assessment : No significant health effects observed in animals at concentra-

tions of 0.2 mg/l/6h/d or less.

#### Repeated dose toxicity

### Components:

### Imidacloprid:

Species : Mouse, male
LOAEL : 17 mg/kg
Application Route : Ingestion
Exposure time : 24 Months

#### Silicic acid, aluminum sodium salt:

 Species
 : Rat

 NOAEL
 : 1.3 mg/m³

 LOAEL
 : 5.9 mg/m³

Application Route : inhalation (dust/mist/fume)

Exposure time : 13 Weeks

Remarks : Based on data from similar materials

## Naphthalenesulfonic acid, bis(1-methylethyl)-, Methyl derivatives, sodium salts:

Species : Rat

NOAEL : 200 mg/kg

LOAEL : 700 mg/kg

Application Route : Ingestion

Exposure time : 54 Days

Method : OECD Test Guideline 422

#### **Aspiration toxicity**

Not classified based on available information.

according to the OSHA Hazard Communication Standard



## **MERIT WP75 4X(4X1.6OZ) CAS US**

Version Date of last issue: 07/26/2023 Revision Date: SDS Number: 2.0 08/25/2023 11251929-00002 Date of first issue: 07/26/2023

#### **SECTION 12. ECOLOGICAL INFORMATION**

#### **Ecotoxicity**

#### **Components:**

Imidacloprid:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 211 mg/l

Exposure time: 96 h

Toxicity to daphnia and other : EC50: 0.0027 mg/l

aquatic invertebrates

Exposure time: 48 h

Toxicity to algae/aquatic

plants

: ErC50 (Desmodesmus subspicatus (green algae)): > 10 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 201

NOEC (Desmodesmus subspicatus (green algae)): >= 10 mg/l

Exposure time: 96 h

Method: OECD Test Guideline 201

Toxicity to fish (Chronic tox-

icity)

NOEC (Oncorhynchus mykiss (rainbow trout)): 9.02 mg/l

Exposure time: 91 d

Method: OECD Test Guideline 210

Toxicity to daphnia and other : EC10: 0.000056 mg/l aquatic invertebrates (Chron-

Toxicity to microorganisms

ic toxicity)

Exposure time: 21 d

: NOEC (activated sludge): 5,600 mg/l

Exposure time: 3 h

#### Silicic acid, aluminum sodium salt:

LL50 (Danio rerio (zebra fish)): 10,000 mg/l Toxicity to fish

Exposure time: 96 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 203

aquatic invertebrates

Toxicity to daphnia and other : EL50 (Daphnia magna (Water flea)): >= 10,000 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 202

Remarks: Based on data from similar materials

Toxicity to algae/aquatic

plants

: EL50 (Desmodesmus subspicatus (green algae)): > 10,000

ma/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

NOELR (Desmodesmus subspicatus (green algae)): 10,000

mg/l

Exposure time: 72 h

according to the OSHA Hazard Communication Standard



## **MERIT WP75 4X(4X1.6OZ) CAS US**

Version SDS Number: Date of last issue: 07/26/2023 Revision Date: 2.0 08/25/2023 11251929-00002 Date of first issue: 07/26/2023

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Naphthalenesulfonic acid, bis(1-methylethyl)-, Methyl derivatives, sodium salts:

Toxicity to daphnia and other :

aquatic invertebrates

EL50 (Daphnia magna (Water flea)): > 100 mg/l

Exposure time: 48 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 202

Toxicity to algae/aquatic

plants

EL50 (Raphidocelis subcapitata (freshwater green alga)): >

100 mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

EL10 (Raphidocelis subcapitata (freshwater green alga)): 14.8

mg/l

Exposure time: 72 h

Test substance: Water Accommodated Fraction

Method: OECD Test Guideline 201

Persistence and degradability

**Components:** 

Imidacloprid:

Biodegradability : Result: not rapidly degradable

Naphthalenesulfonic acid, bis(1-methylethyl)-, Methyl derivatives, sodium salts:

Biodegradability Result: Not readily biodegradable.

> Biodegradation: 0 % Exposure time: 28 d

Method: OECD Test Guideline 301D

Bioaccumulative potential

**Components:** 

Imidacloprid:

Partition coefficient: n-

: log Pow: 0.57

octanol/water

Naphthalenesulfonic acid, bis(1-methylethyl)-, Methyl derivatives, sodium salts:

Partition coefficient: n-

octanol/water

: log Pow: 0

Mobility in soil

No data available

according to the OSHA Hazard Communication Standard



## MERIT WP75 4X(4X1.6OZ) CAS US

Version Revision Date: SDS Number: Date of last issue: 07/26/2023 2.0 08/25/2023 11251929-00002 Date of first issue: 07/26/2023

#### Other adverse effects

No data available

#### **SECTION 13. DISPOSAL CONSIDERATIONS**

Disposal methods

Waste from residues : It is best to use all of the product in accordance with label

directions. If it is necessary to dispose of unused product, please follow container label instructions and applicable local

guidelines.

Do not dispose of waste into sewer.

Contaminated packaging : Follow advice on product label and/or leaflet.

Empty containers retain residue and can be dangerous.

Do not re-use empty containers.

#### **SECTION 14. TRANSPORT INFORMATION**

#### International Regulations

**UNRTDG** 

UN number : UN 3077

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.

(Imidacloprid)

Class : 9
Packing group : III
Labels : 9
Environmentally hazardous : yes

**IATA-DGR** 

UN/ID No. : UN 3077

Proper shipping name : Environmentally hazardous substance, solid, n.o.s.

(Imidacloprid)

Class : 9

Packing group : III

Labels : Miscellaneous

Packing instruction (cargo :

aircraft)

Packing instruction (passen: :

: 956

956

ger aircraft)

Environmentally hazardous : yes

**IMDG-Code** 

UN number : UN 3077

Proper shipping name : ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID,

N.O.S.

(Imidacloprid)
Class : 9

Packing group : III Labels : 9 EmS Code : F-A, S-F

Marine pollutant : yes

according to the OSHA Hazard Communication Standard



## MERIT WP75 4X(4X1.6OZ) CAS US

Version Revision Date: SDS Number: Date of last issue: 07/26/2023 2.0 08/25/2023 11251929-00002 Date of first issue: 07/26/2023

#### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

#### **Domestic regulation**

**49 CFR** 

UN/ID/NA number : UN 3077

Proper shipping name : Environmentally hazardous substance, solid, n.o.s.

(Imidacloprid)

Class : 9 Packing group : III

Labels : CLASS 9 ERG Code : 171

Marine pollutant : yes(Imidacloprid)

Remarks : Above applies only to containers over 119 gallons or 450 li-

ters.

Shipment by ground under DOT is non-regulated; however it may be shipped per the applicable hazard classification to facilitate multi-modal transport involving ICAO (IATA) or IMO.

#### Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

#### **SECTION 15. REGULATORY INFORMATION**

### **CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

#### SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

### SARA 302 Extremely Hazardous Substances Threshold Planning Quantity

This material does not contain any components with a section 302 EHS TPQ.

SARA 311/312 Hazards : Combustible dust

Acute toxicity (any route of exposure)

SARA 313 : This material does not contain any chemical components with

known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

#### **US State Regulations**

#### Pennsylvania Right To Know

Imidacloprid 138261-41-3
Silicic acid, aluminum sodium salt 1344-00-9
Lignosulfonic acid, sodium salt 8061-51-6
Naphthalenesulfonic acid, bis(1-methylethyl)-, Methyl deriva-68909-82-0

tives, sodium salts

Product Type : Insecticides, acaricides and products to control other arthro-

according to the OSHA Hazard Communication Standard



## **MERIT WP75 4X(4X1.6OZ) CAS US**

Version Revision Date: SDS Number: Date of last issue: 07/26/2023 2.0 08/25/2023 11251929-00002 Date of first issue: 07/26/2023

Active substance pods


75 %

Imidacloprid

#### **SECTION 16. OTHER INFORMATION**

#### **Further information**

#### NFPA 704:



Special hazard

#### HMIS® IV:



HMIS® ratings are based on a 0-4 rating scale, with 0 representing minimal hazards or risks, and 4 representing significant hazards or risks. The "\*" represents a chronic hazard, while the "/" represents the absence of a chronic hazard.

#### Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)

CAL PEL : California permissible exposure limits for chemical contami-

nants (Title 8, Article 107)

OSHA Z-3 : USA. Occupational Exposure Limits (OSHA) - Table Z-3 Min-

eral Dusts

ACGIH / TWA : 8-hour, time-weighted average CAL PEL / PEL : Permissible exposure limit OSHA Z-3 / TWA : 8-hour time weighted average

AllC - Australian Inventory of Industrial Chemicals; ASTM - American Society for the Testing of Materials; bw - Body weight; CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DOT - Department of Transportation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; EHS - Extremely Hazardous Substance; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; HMIS - Hazardous Materials Identification System; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime

according to the OSHA Hazard Communication Standard



## MERIT WP75 4X(4X1.6OZ) CAS US

 Version
 Revision Date:
 SDS Number:
 Date of last issue: 07/26/2023

 2.0
 08/25/2023
 11251929-00002
 Date of first issue: 07/26/2023

Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; MSHA - Mine Safety and Health Administration; n.o.s. - Not Otherwise Specified; NFPA - National Fire Protection Association; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; RCRA - Resource Conservation and Recovery Act; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; RQ - Reportable Quantity; SADT - Self-Accelerating Decomposition Temperature; SARA - Superfund Amendments and Reauthorization Act; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TECI - Thailand Existing Chemicals Inventory; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative

Sources of key data used to compile the Material Safety

Data Sheet

Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agen-

cy, http://echa.europa.eu/

Revision Date : 08/25/2023

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

US / Z8