

NET WT. 50 LBS. (22.7 Kg)

NX-PRO® FERTILIZER

16-0-30



Greens Grade Fertilizer

GUARANTEED ANALYSIS

Total Nitrogen (N)	16%
2.5% Water Insoluble Nitrogen*	
9.1% Urea Nitrogen	
4.4% Other Water Soluble Nitrogen*	
Soluble Potash (K ₂ O)	30%
Sulfur (S)	9.8%
9.8% Combined Sulfur (S)	
Iron (Fe)	1.0%
0.01% Water Soluble Iron (Fe)	
Manganese (Mn)	0.7%
0.10% Water Soluble Manganese (Mn)	

Derived From: Methylene Ureas, Urea, Sulfate of Potash, Iron Sulfate, Manganese Sulfate.

Chlorine (Cl) not more than 2.0%

*6.9% Slowly Available Nitrogen from Methylene Ureas.

F699

NOTICE: This product contains the secondary nutrient iron. Iron may stain concrete surfaces and should not be applied on dry or water dampened concrete and should be removed from these areas promptly after application by sweeping or blowing. Do not wash off with water.

52010

APPLICATION RATES:

To feed at the rate of 1 lb. Soluble Potash per 1,000 sq. ft. apply this product at 3.4 lbs. per 1,000 sq. ft. or 148 lbs. per acre. To feed at the rate of 1/2 lb. Potassium per 1,000 sq. ft. apply this product at 1.7 lbs. per 1,000 sq. ft. or 74 lbs. per acre.

PRECAUTIONARY STATEMENT:

Fertilizer may cause irritation of eyes, nose, throat, and skin. In case of contact with skin or eyes, flush with plenty of water; for eyes, get medical attention.

**KEEP OUT OF REACH OF CHILDREN
CAUTION**

SUGGESTED SPREADER SETTINGS

Spreader	Speed		Width of Coverage	Settings	
	Ground MPH	PTO RPM		3.4 lbs. (1# K O)	1.7 lbs. (1/2 # K O)
PennMulch HVO ProScape SS	3		8 ft.	G	C
Cyclone	3		8 ft.	2 1/2	2
Earthway Rotary	3		8 ft.	10	8
Ezee Flow (109)	5	540	30 ft.	C1	A2
Gandy	3			21	19
Lely (HR,1250,1500,2010)	5		39 ft.	2 1/2 II	2II
Lely (W)	5	425	39 ft.	2 1/2 II	2II
Lesco (letters)	3		8 ft.	D	C
Lesco (numeric)	3		8 ft.	9	7
Ortho Rotary	3		6 ft.	1 1/2	1 1/2
Prizelawn BF & CBR III	3		8 ft.	G	C
Prizelawn CBR III	3		8 ft.	2	1 1/2
Prizelawn LF-1	3		8 ft.	2	1 1/2
Republic Rotary	3		6 ft.	2	1 1/2
Scotts AccuPro	3		8 ft.	E	D
Scotts (Rotary) R7X	3		8 ft.	D	C
Scotts (Rotary) R8A	3		8 ft.	I	G
Spyker	3		8 ft.	2	1 1/2
Vicon (all models)	5	540	35 ft.	21	17

These settings were calibrated and field tested. However, age and condition of spreader, speed of operation, and evenness of terrain may require slightly different settings for desired coverage.

Manufactured by:
LEBANON SEABOARD CORPORATION
1600 East Cumberland Street
Lebanon, PA 17042
www.LebanonTurf.com



NX-PRO® is a registered trademark of Lebanon Seaboard Corporation

Information regarding the contents and levels of metals in this product is available on the Internet at <http://www.regulatory-info-lebsea.com>

03-09-11

16-0-30



Greens Grade Fertilizer

GUARANTEED ANALYSIS

Total Nitrogen (N)	16%
2.5% Water Insoluble Nitrogen*	
9.1% Urea Nitrogen	
4.4% Other Water Soluble Nitrogen*	
Soluble Potash (K ₂ O)	30%
Sulfur (S)	9.8%
9.8% Combined Sulfur (S)	
Iron (Fe)	1.0%
0.01% Water Soluble Iron (Fe)	
Manganese (Mn)	0.7%
0.10% Water Soluble Manganese (Mn)	

Derived From: Methylene Ureas, Urea, Sulfate of Potash, Iron Sulfate, Manganese Sulfate.

Chlorine (Cl) not more than 2.0%

*6.9% Slowly Available Nitrogen from Methylene Ureas.

F699

52010

NOTICE: This product contains the secondary nutrient iron. Iron may stain concrete surfaces and should not be applied on dry or water dampened concrete and should be removed from these areas promptly after application by sweeping or blowing. Do not wash off with water.

APPLICATION RATES:

To feed at the rate of 1 lb. Soluble Potash per 1,000 sq. ft. apply this product at 3.4 lbs. per 1,000 sq. ft. or 148 lbs. per acre. To feed at the rate of 1/2 lb. Potassium per 1,000 sq. ft. apply this product at 1.7 lbs. per 1,000 sq. ft. or 74 lbs. per acre.

PRECAUTIONARY STATEMENT:

Fertilizer may cause irritation of eyes, nose, throat, and skin. In case of contact with skin or eyes, flush with plenty of water; for eyes, get medical attention.

**KEEP OUT OF REACH
OF CHILDREN
CAUTION**

SUGGESTED SPREADER SETTINGS

Spreader	Speed		Width of Coverage	Settings	
	Ground MPH	PTO RPM		3.4 lbs. (1# K O)	1.7 lbs. (1/2 # K O)
PennMulch HVO ProScope SS	3		8 ft.	G	C
Cyclone	3		8 ft.	2 1/2	2
Earthway Rotary	3		8 ft.	10	8
Ezee Flow (109)	5	540	30 ft.	C1	A2
Gandy	3			21	19
Lely (HR,1250,1500,2010)	5		39 ft.	2 1/2 II	2II
Lely (W)	5	425	39 ft.	2 1/2 II	2II
Lesco (letters)	3		8 ft.	D	C
Lesco (numeric)	3		8 ft.	9	7
Ortho Rotary	3		6 ft.	1 1/2	1 1/2
Prizelawn BF & CBR III	3		8 ft.	G	C
Prizelawn CBR III	3		8 ft.	2	1 1/2
Prizelawn LF-1	3		8 ft.	2	1 1/2
Republic Rotary	3		6 ft.	2	1 1/2
Scotts AccuPro	3		8 ft.	E	D
Scotts (Rotary) R7X	3		8 ft.	D	C
Scotts (Rotary) R8A	3		8 ft.	1	G
Spyker	3		8 ft.	2	1 1/2
Vicon (all models)	5	540	35 ft.	21	17

These settings were calibrated and field tested. However, age and condition of spreader, speed of operation, and evenness of terrain may require slightly different settings for desired coverage.

Manufactured by:
LEBANON SEABOARD CORPORATION
 1600 East Cumberland Street
 Lebanon, PA 17042
www.LebanonTurf.com



NX-PRO® is a registered trademark of Lebanon Seaboard Corporation

Information regarding the contents and levels of metals in this product is available on the Internet at <http://www.regulatory-info-lebsea.com>