



Peak Windshield Wash & Deicer -20 °F

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product form : Mixture
Product name : Peak Windshield Wash & Deicer -20 °F

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of the substance/mixture : Windshield Wash Fluid

1.3. Details of the supplier of the safety data sheet

Old World Industries, LLC
4065 Commercial Ave.
Northbrook, IL 60062 - USA
T (847) 559-2000
www.oldworldind.com

1.4. Emergency telephone number

Emergency number : (800) 424-9300; (703) 527 3887 (International)
Chemtrec

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

GHS-US classification

Flam. Liq. 2	H225
Acute Tox. 4 (Oral)	H302
Acute Tox. 3 (Dermal)	H311
Acute Tox. 4 (Inhalation:dust,mist)	H332
STOT SE 1	H370

Full text of H-phrases: see section 16

2.2. Label elements

GHS-US labelling

Hazard pictograms (GHS-US) :



GHS02

GHS06

GHS08

Signal word (GHS-US) : Danger

Hazard statements (GHS-US) : H225 - Highly flammable liquid and vapor
H302+H332 - Harmful if swallowed or if inhaled
H311 - Toxic in contact with skin
H370 - Causes damage to organs (May cause blindness if swallowed)

Precautionary statements (GHS-US) : P201 - Obtain special instructions before use
P202 - Do not handle until all safety precautions have been read and understood
P210 - Keep away from heat, hot surfaces, open flames, sparks. - No smoking
P233 - Keep container tightly closed
P240 - Ground/bond container and receiving equipment
P241 - Use explosion-proof electrical, lighting, ventilating equipment
P242 - Use only non-sparking tools
P243 - Take precautionary measures against static discharge
P260 - Do not breathe mist, spray, vapors
P264 - Wash affected areas thoroughly after handling
P270 - Do not eat, drink or smoke when using this product
P271 - Use only outdoors or in a well-ventilated area
P280 - Wear personal protective equipment as required
P301+P310 - If swallowed: Immediately call doctor/physician or poison center . Rinse Mouth
P303+P361+P353 - If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
P304+P340 - If inhaled: Remove person to fresh air and keep comfortable for breathing
P305+P351+P338 - If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing

Peak Windshield Wash & Deicer -20 °F

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

P314 - Get medical advice/attention if you feel unwell
P361+P364 - Take off immediately all contaminated clothing and wash it before reuse
P370+P378 - In case of fire: Use Foam, Sand, Dry powder, Carbon dioxide to extinguish
P403+P235 - Store in a well-ventilated place. Keep cool
P405 - Store locked up
P501 - Dispose of contents/container, in a safe manner, to appropriate waste disposal facility, in accordance with local/regional/national/international regulations

2.3. Other hazards

No additional information available

2.4. Unknown acute toxicity (GHS US)

No data available

SECTION 3: Composition/information on ingredients

3.1. Substance

Not applicable

3.2. Mixture

Name	Product identifier	% by wt	GHS-US classification
methanol	(CAS No) 67-56-1	< 33	Flam. Liq. 2, H225 Acute Tox. 3 (Inhalation), H331 STOT SE 1, H370

SECTION 4: First aid measures

4.1. Description of first aid measures

First-aid measures general	: Never give anything by mouth to an unconscious person. If you feel unwell, seek medical advice (show the label where possible).
First-aid measures after inhalation	: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Seek immediate medical advice. Allow the victim to rest. If not breathing, give artificial respiration. If breathing is difficult, give oxygen.
First-aid measures after skin contact	: Wash immediately with lots of water. Soap may be used. Do not apply (chemical) neutralizing agents. Remove clothing before washing. Consult a doctor/medical service.
First-aid measures after eye contact	: Remove contact lenses, if present and easy to do. Continue rinsing. Rinse immediately with plenty of water for 15 minutes, lifting lower and upper lids. Take victim to an ophthalmologist if irritation persists.
First-aid measures after ingestion	: Obtain emergency medical attention. Rinse mouth. Never give anything by mouth to an unconscious person.

4.2. Most important symptoms and effects, both acute and delayed

Symptoms/injuries after inhalation	: May cause irritation of the nose and throat. High concentrations may cause acute central nervous system depression characterized by headaches, dizziness, nausea and confusion.
Symptoms/injuries after skin contact	: Prolonged exposure to skin may cause skin irritation experienced as burning, dryness, cracking and redness.
Symptoms/injuries after eye contact	: May cause severe irritation.
Symptoms/injuries after ingestion	: May cause nausea, abdominal pain, headache, shortness of breath, visual impairment and blindness. Severe poisoning can lead to coma and death.
Chronic symptoms	: ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Red skin. Dry skin. Skin rash/inflammation. Headache. Feeling of weakness. Disturbed tactile sensibility. Visual disturbances. Sleeplessness. Gastrointestinal complaints. Cardiac and blood circulation effects.

4.3. Indication of any immediate medical attention and special treatment needed

This product contains methanol which can cause intoxication and depression of the central nervous system. Methanol is metabolized to formic acid and formaldehyde. These metabolites can cause metabolic acidosis, visual disturbances and blindness. Since metabolism is required for these toxic symptoms, their onset may be delayed from 6 to 30 hours following ingestion.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media	: ABC powder. Foam. Dry powder. Carbon dioxide. Sand.
Unsuitable extinguishing media	: Do not use a heavy water stream.

5.2. Special hazards arising from the substance or mixture

Fire hazard	: Flammable liquid and vapor. Vapors are heavier than air and may travel along the ground or may be moved by ventilation.
-------------	---

Peak Windshield Wash & Deicer -20 °F

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Explosion hazard : Heat may build pressure, rupturing closed containers, spreading fire and increasing risk of burns and injuries.

5.3. Advice for firefighters

Firefighting instructions : Use water spray or fog for cooling exposed containers. Exercise caution when fighting any chemical fire. Prevent fire-fighting water from entering environment.

Protection during firefighting : Do not enter fire area without proper protective equipment, including respiratory protection.

Special protective equipment for fire fighters : Wear positive pressure self-contained breathing apparatus (SCBA). Protective fire fighting clothing (includes fire-fighting helmet, coat, pants, boots and gloves).

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

General measures : Remove ignition sources. Use special care to avoid static electric charges. Do not breathe vapor or mist. Wear appropriate respirator when ventilation is inadequate.

6.1.1. For non-emergency personnel

Emergency procedures : Evacuate unnecessary personnel. Keep upwind. Mark the danger area.

6.1.2. For emergency responders

Protective equipment : Equip cleanup crew with proper protection.

Emergency procedures : Ventilate area.

6.2. Environmental precautions

Prevent entry to sewers and public waters. Notify authorities if liquid enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

For containment : Contain released substance, pump into suitable containers. Dam up the liquid spill. Plug the leak, cut off the supply. Try to reduce evaporation. Take account of toxic/corrosive precipitation water. Dilute combustible/toxic gases/vapors with water spray.

Methods for cleaning up : Soak up spills with inert solids, such as clay or diatomaceous earth as soon as possible. Collect spillage. Store away from other materials.

6.4. Reference to other sections

See Heading 8. Exposure controls and personal protection.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Additional hazards when processed : In use, may form flammable vapor-air mixture.

Precautions for safe handling : Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Provide good ventilation in process area to prevent formation of vapor.

Hygiene measures : Wash contaminated clothing before reuse.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Use explosion-proof electrical, lighting, ventilating equipment. Ground/bond container and receiving equipment. Proper grounding procedures to avoid static electricity should be followed.

Storage conditions : Keep only in the original container in a cool, well ventilated place away from : Heat sources, hot surfaces, open flames, sparks. Keep container closed when not in use. Do not store near food, foodstuffs, drugs or potable water supplies.

Incompatible products : Keep away from strong acids, strong bases and oxidizing agents.

Incompatible materials : Sources of ignition.

7.3. Specific end use(s)

No additional information available

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

methanol (67-56-1)		
ACGIH	ACGIH TWA (ppm)	200 ppm (Skin)
ACGIH	ACGIH STEL (ppm)	250 ppm (Skin)
ACGIH	Remark (ACGIH)	Headache; eye dam; dizziness; nausea
OSHA	OSHA PEL (TWA) (mg/m ³)	260 mg/m ³ (Skin)

Peak Windshield Wash & Deicer -20 °F

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

methanol (67-56-1)

OSHA	OSHA PEL (TWA) (ppm)	200 ppm (Skin)
------	----------------------	----------------

8.2. Exposure controls

Personal protective equipment : Avoid all unnecessary exposure. Gloves. Safety glasses.



Hand protection : Wear protective gloves.
Eye protection : Chemical goggles or safety glasses.
Skin and body protection : Wear suitable protective clothing.
Respiratory protection : In case of inadequate ventilation wear respiratory protection. Wear appropriate mask.
Other information : Do not eat, drink or smoke during use.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state : Liquid
Color : Blue
Odor : alcohol odor
Odor threshold : No data available
Relative evaporation rate (butylacetate=1) : Greater than n-butyl acetate
Freezing point : No data available
Boiling point : 80 - 83 °C (177 - 181 °F)
Flash point : 33 °C (92 °F)
Auto-ignition temperature : No data available
Decomposition temperature : No data available
Flammability (solid, gas) : No data available
Vapor pressure : 43 mm Hg @ 20 °C
Relative vapor density at 20 °C : Heavier than air
Specific Gravity : 0.96 @ 20 °C
Solubility : Water: Complete
Log Pow : No data available
Log Kow : No data available
Viscosity, kinematic : No data available
Viscosity, dynamic : No data available
Explosive properties : No data available
Oxidizing properties : No data available
Explosive limits : 6 - 36 vol %

9.2. Other information

VOC content : < 33.00 %

SECTION 10: Stability and reactivity

10.1. Reactivity

No additional information available

10.2. Chemical stability

Stable.

10.3. Possibility of hazardous reactions

Hazardous polymerization will not occur.

10.4. Conditions to avoid

Sources of ignition.

Peak Windshield Wash & Deicer -20 °F

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.5. Incompatible materials

Keep away from strong acids, strong bases and oxidizing agents.

10.6. Hazardous decomposition products

Fume. Carbon monoxide. Carbon dioxide.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Oral: Harmful if swallowed. Dermal: Toxic in contact with skin. Inhalation:dust,mist: Harmful if inhaled.

methanol (67-56-1)	
LD50 oral rat	> 5,000.00 mg/kg (Rat; BASF test; Literature study; 1187-2769 mg/kg bodyweight; Rat; Weight of evidence)
LD50 dermal rabbit	15,800.00 mg/kg (Rabbit; Literature study)
LC50 inhalation rat (mg/l)	85.00 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	64,000.00 ppm/4h (Rat; Literature study)
ATE US (dermal)	15,800.00 mg/kg bodyweight
ATE US (gases)	700.00 ppmv/4h
ATE US (vapors)	3.00 mg/l/4h
ATE US (dust,mist)	0.50 mg/l/4h

Skin corrosion/irritation : Not classified

Serious eye damage/irritation : Not classified

Respiratory or skin sensitisation : Not classified

Germ cell mutagenicity : Not classified

Carcinogenicity : Not classified

Reproductive toxicity : Not classified

Specific target organ toxicity (single exposure) : Causes damage to organs (May cause blindness if swallowed) .

Specific target organ toxicity (repeated exposure) : Not classified

Aspiration hazard : Not classified

Symptoms/injuries after inhalation : May cause irritation of the nose and throat. High concentrations may cause acute central nervous system depression characterized by headaches, dizziness, nausea and confusion.

Symptoms/injuries after skin contact : Prolonged exposure to skin may cause skin irritation experienced as burning, dryness, cracking and redness.

Symptoms/injuries after eye contact : May cause severe irritation.

Symptoms/injuries after ingestion : May cause nausea, abdominal pain, headache, shortness of breath, visual impairment and blindness. Severe poisoning can lead to coma and death.

Chronic symptoms : ON CONTINUOUS/REPEATED EXPOSURE/CONTACT: Red skin. Dry skin. Skin rash/inflammation. Headache. Feeling of weakness. Disturbed tactile sensibility. Visual disturbances. Sleeplessness. Gastrointestinal complaints. Cardiac and blood circulation effects.

SECTION 12: Ecological information

12.1. Toxicity

methanol (67-56-1)	
LC50 fish 1	15,400.00 mg/l (96 h; Lepomis macrochirus; Lethal)
EC50 Daphnia 1	> 10,000.00 mg/l (48 h; Daphnia magna; Lethal)
LC50 fish 2	10,800.00 mg/l 96 h; Salmo gairdneri (Oncorhynchus mykiss)
EC50 Daphnia 2	24,500.00 mg/l (48 h; Daphnia magna; Locomotor effect)
Threshold limit other aquatic organisms 1	6600 mg/l (16 h; Pseudomonas putida)
Threshold limit algae 1	530 mg/l (192 h; Microcystis aeruginosa)
Threshold limit algae 2	8000 mg/l (168 h; Scenedesmus quadricauda)

12.2. Persistence and degradability

Peak Windshield Wash & Deicer -20 °F

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

methanol (67-56-1)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Highly mobile in soil.
Biochemical oxygen demand (BOD)	0.6 - 1.12 g O ₂ /g substance
Chemical oxygen demand (COD)	1.42 g O ₂ /g substance
ThOD	1.50 g O ₂ /g substance
BOD (% of ThOD)	0.80 % ThOD

12.3. Bioaccumulative potential

methanol (67-56-1)	
BCF fish 1	< 10.00 (72 h; Leuciscus idus)
BCF fish 2	1.00 (72 h; Cyprinus carpio; Blood)
Log Pow	-0.77 (Experimental value; Other)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

12.4. Mobility in soil

methanol (67-56-1)	
Surface tension	0.02 N/m (20 °C)

12.5. Other adverse effects

Effect on ozone layer	: No known effect on the ozone layer
Effect on global warming	: No known ecological damage caused by this product.
Other information	: Avoid release to the environment.

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Waste disposal recommendations	: Dispose of contents/container, in a safe manner, to appropriate waste disposal facility, in accordance with local/regional/national/international regulations.
Ecology - waste materials	: Avoid release to the environment.

SECTION 14: Transport information

In accordance with DOT

Transport document description	: UN1993 Flammable liquids, n.o.s. (Methanol), 3, III
UN-No.(DOT)	: 1993
DOT NA no.	: UN1993
Proper Shipping Name (DOT)	: Flammable liquids, n.o.s. Methanol
Transport hazard class(es) (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Hazard labels (DOT)	: 3 - Flammable liquid



DOT Symbols	: G - Identifies PSN requiring a technical name
Packing group (DOT)	: III - Minor Danger
DOT Packaging Exceptions (49 CFR 173.xxx)	: 150
DOT Packaging Non Bulk (49 CFR 173.xxx)	: 203
DOT Packaging Bulk (49 CFR 173.xxx)	: 242
DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27)	: 60 L
DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75)	: 220 L
DOT Vessel Stowage Location	: A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

Peak Windshield Wash & Deicer -20 °F

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Other information : In inner packaging no more than 5.0 L: Proper Shipping Name: Limited Quantity of Class III Per 49 CFR Part 173.10 (PG III, inner packaging no more than 5.0L).

ADR

No additional information available

Transport by sea

UN-No. (IMDG) : 1993
Proper Shipping Name (IMDG) : FLAMMABLE LIQUID, N.O.S. (Methanol)
Class (IMDG) : 3 - Flammable liquids
Packing group (IMDG) : III - substances presenting low danger
Limited quantities (IMDG) : In Non-Bulk quantities with inner packaging no more than 5.0L: Proper Shipping Name: Dangerous Goods in Limited Class 3 (Windshield Wash Containing Methanol) Packages or pallets must be marked "Dangerous Goods in Limited Quantities of Class 3" Outer Package cannot weigh more than 30 kg.

Air transport

UN-No. (IATA) : 1993
Proper Shipping Name (IATA) : FLAMMABLE LIQUID, N.O.S. (Methanol)
Class (IATA) : 3 - Flammable Liquids
Packing group (IATA) : III - Minor Danger
Instruction "passenger" - Limited quantities (ICAO) : Y309 (Max qty. per package 10L) Special Provision A3

SECTION 15: Regulatory information

15.1. US Federal regulations

Peak Windshield Wash & Deicer -20 °F	
EPA TSCA Regulatory Flag	Toxic Substances Control Act (TSCA): The intentional ingredients of this product are listed
SARA Section 302 Threshold Planning Quantity (TPQ)	None
SARA Section 311/312 Hazard Classes	Delayed (chronic) health hazard Fire hazard Immediate (acute) health hazard
SARA Section 313 - Emission Reporting	33 % (Methanol CAS # 67-56-1)
methanol (67-56-1)	
Listed on the United States TSCA (Toxic Substances Control Act) inventory Listed on United States SARA Section 313	
RQ (Reportable quantity, section 304 of EPA's List of Lists)	5000 lb(s)

15.2. International regulations

CANADA

WHMIS Classification



Class B Division 2 -
Flammable Liquid



Class D Division 1
Subdivision A - Very
toxic material
causing immediate
and serious toxic
effects

EU-Regulations

No additional information available

Classification according to Regulation (EC) No. 1272/2008 [CLP]

No additional information available

Peak Windshield Wash & Deicer -20 °F

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Classification according to Directive 67/548/EEC [DSD] or 1999/45/EC [DPD]

Not classified

National regulations

Peak Windshield Wash & Deicer -20 °F

DSL (Canada): The intentional ingredients of this product are listed
ECL (South Korea): The intentional ingredients of this product are listed.
EINECS (Europe): The intentional ingredients of this product are listed
ENCS (Japan): The intentional ingredients of this product are listed

15.3. US State regulations

methanol (67-56-1)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significance risk level (NSRL)
No	Yes	No	No	

methanol (67-56-1)

U.S. - Massachusetts - Right To Know List
U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Full text of H-phrases:

Acute Tox. 3 (Dermal)	Acute toxicity (dermal), Category 3
Acute Tox. 3 (Inhalation)	Acute toxicity (inhal.), Category 3
Acute Tox. 4 (Inhalation:dust,mist)	Acute toxicity (inhalation:dust,mist) Category 4
Acute Tox. 4 (Oral)	Acute toxicity (oral), Category 4
Flam. Liq. 2	Flammable liquids, Category 2
STOT SE 1	Specific target organ toxicity — single exposure, Category 1
H225	Highly flammable liquid and vapor
H302	Harmful if swallowed
H311	Toxic in contact with skin
H331	Toxic if inhaled
H332	Harmful if inhaled
H370	Causes damage to organs

NFPA health hazard


: 1 - Exposure could cause irritation but only minor residual injury even if no treatment is given.

NFPA fire hazard

: 3 - Liquids and solids that can be ignited under almost all ambient conditions.

NFPA reactivity

: 0 - Normally stable, even under fire exposure conditions, and are not reactive with water.



HMIS III Rating

Health

: 2 Moderate Hazard - Temporary or minor injury may occur

Flammability

: 3 Serious Hazard - Materials capable of ignition under almost all normal temperature conditions. Includes flammable liquids with flash points below 73 °F (22 °C) and boiling points above 100 °F (37 °C). as well as liquids with flash points between 73 °F (22 °C) and 100 °F (37 °C). (Classes IB & IC)

Physical

: 0 Minimal Hazard - Materials that are normally stable, even under fire conditions, and will NOT react with water, polymerize, decompose, condense, or self-react. Non-Explosives.

Personal Protection

A - Safety glasses

Peak Windshield Wash & Deicer -20 °F

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SDS GHS US (GHS HazCom 2012) OWI

Old World Industries, LLC makes no warranty, representation or guarantee as to the accuracy, sufficiency or completeness of the material set forth herein. It is the user's responsibility to determine the safety, toxicity and suitability of his own use, handling and disposal of this product. Since actual use by others is beyond our control, no warranty, expressed or implied, is made by Old World Industries, LLC as to the effects of such use, the results to be obtained or the safety and toxicity of this product, nor does Old World Industries, LLC assume liability arising out of the use by others of this product referred to herein. The data in this SDS relates only to the specific material designated herein and does not relate to use in combination with any other material or in any process.