# Tim-bor Professional INSECTICIDE AND FUNGICIDE

A preservative for protection and treatment of wood against fungal decay and wood destroying insects including termites

For the prevention and remedial control of wood\*\* infesting organisms including: Termites, Drywood Termites, Wood Destroying Beetles, Decay Fungi and Carpenter Ants \*\*Also for Wood Foam Composite Structural Components

NET WT.: 25 LBS.



#### 

EPA Reg. No. 64405-8

EPA Est. 64405-TN-1

## Keep Out of Reach of Children **CAUTION**

SEE SIDE PANEL FOR FIRST AID, PRECAUTIONARY STATEMENTS AND COMPLETE DIRECTIONS FOR USE.

#### First Aid

If Swallowed:	<ul> <li>Immediately call a poison control center or doctor for treatment advice.</li> <li>Have person sip a glass of water if able to swallow.</li> <li>Do not induce vomiting unless told to do so by the poison control center or doctor.</li> <li>Do not give anything by mouth to an unconscious person.</li> </ul>
If Inhaled:	Move person to fresh air.     If person is not breathing, call 911 or an ambulance, then give artificial respiration, preferably by mouth-to-mouth, if possible.     Call a poison control center or doctor for further treatment advice.
If in Eyes:	Hold eye open and rinse slowly and gently with water for 15-20 minutes.     Remove contact lenses, if present, after the first 5 minutes, then continue rinsing eye.     Call a poison control center or doctor for further treatment advice.

Have the product container or label with you when calling a poison control center or doctor or going for treatment.

### PRECAUTIONARY STATEMENTS Hazards To Humans & Domestic Animals

**CAUTION:** Harmful if swallowed or inhaled. Causes moderate eye irritation. Avoid contact with eyes or clothing. Avoid breathing dust. Thoroughly wash with soap and water after handling. Remove contaminated clothing and wash clothing before reuse.

#### Personal Protective Equipment (PPE)

Some materials that are chemical-resistant to this product are barrier laminate; butyl, nitrile, neoprene and natural rubbers  $\geq$  14 mils; polyethylene; polyvinyl chloride; and viton  $\geq$  14 mils. If you want more options, follow the instructions for category C on an EPA chemical-resistance category selection chart.

Applicators, mixers and other handlers must wear long-sleeved shirt, long pants, socks, shoes, chemical-resistant gloves and protective eyewear. When applying this product in confined spaces, provide ventilation or an exhaust system; or use a NIOSH-approved dust/mist filtering respirator (MSHA/NIOSH approval number prefix TC-21C) with a prefilter approved for pesticides (MSHA/NIOSH approval prefix TC-23C); or use a canister approved for pesticides (MSHA/NIOSH approval prefix TC-14G) or a NIOSH-approved respirator with any N, R, P, or HE prefilter.

#### **User Safety Requirements**

Follow manufacturer's instructions for cleaning/maintaining PPE. If no such instructions for washables exist, use detergent and hot water. Keep and wash PPE separately from other laundry.

#### User Safety Recommendations

Users should:

- Wash hands before eating, drinking, chewing gum, using tobacco or using the toilet:
- Remove clothing immediately if pesticide gets inside, then wash thoroughly and put on clean clothing;
- Remove PPE immediately after handling this product. Wash the outside of gloves before removing. As soon as possible, wash thoroughly and change into clean clothing.

#### **Environmental Hazards**

Wood treatment facilities must take steps to prevent runoff of the product into the waterway. Treated material stored outdoors within 100 feet of a pond, lake, stream or river must be covered, surrounded by a containment berm or otherwise protected to prevent surface water runoff. The containment berm must be of sufficient height to prevent runoff during heavy rainfall events.

This pesticide is toxic to fish and wildlife. Do not apply directly to water, to areas where surface water is present or to intertidal areas below the mean high water mark. Do not contaminate water when cleaning equipment or disposing of equipment washwaters.

#### NOTICE

Read and understand the entire label before using.
Use only according to label directions.

Before buying or using this product, read the *Warranty Disclaimer* and *Limitation of Remedies* statements found elsewhere on this label. If terms are unacceptable, return unopened package to seller for full refund of purchase price. Otherwise, use by the buyer or any other user constitutes acceptance of the terms under the *Warranty Disclaimer* and *Limitation of Remedies*.

#### **DIRECTIONS FOR USE**

It is a violation of Federal law to use this product in a manner inconsistent with its labeling.

For applications to tree stumps, do not apply dust directly to stumps; instead mix dust and water and then spray onto the stumps.

#### Product Information

TIM-BOR Professional is a water soluble, inorganic borate salt with insecticidal and fungicidal properties effective against wood-destroying organisms including the target pests listed below. Apply TIM-BOR Professional as a liquid solution, powder or foam. TIM-BOR Professional is an effective treatment for wood (and wood-foam composite structural components) to kill and prevent infestations of

decay fungi including white rot, brown rot (i.e., Poria) and wet rots. This product may be used for preventative treatment (before signs of infestation), for wood in existing structures and for remedial treatment of infested wood in existing structures. TIM-BOR Professional is also effective for the prevention and control of wood destroying insects such as, but not limited to, the following organisms: Subterranean Termites (Reticulitermes, Heterotermes, Coptotermes (Formosan)), Drywood Termites (Kalotermes, Incisitermes), Dampwood Termites (Zootermopsis), Powderpost Beetles (Lyctinae, Bostrichidae), Deathwatch and Furniture Beetles (Anobiidae), Old House Borers, Longhorned Beetles (Cerambycidae), Carpenter Ants (Camponotus), Bark and Timber Beetles.

TIM-BOR Professional is recommended for wood and cellulose material in accordance with the specific treatment methods described herein. TIM-BOR Professional is effective for all interior and exterior wood (and wood-foam composite structural components) that will be protected from excessive rain and not in direct contact with the soil. Types of wood include, but are not limited to, all types of lumber, logs and plywood. This product kills wood-destroying organisms. Some etching of treated wood may occur from organisms before they die. Do not apply TIM-BOR Professional to wood or cellulose material that has been painted, varnished or sealed. For best results, apply TIM-BOR Professional to bare wood. Use soap and water to clean application equipment.

**Note:** Spraying water on some wood species can mobilize natural wood extractives, raise the grain and leave behind calcium or other deposits. Prior to treating large areas, treat a small area with TIM-BOR Professional solution to ensure that you are satisfied with the final aesthetics.

#### **Preparation of Treatment Solutions**

10% TIM-BOR Professional Liquid Solution: To prepare solution, add approximately 80% of the required volume of water to the mixing vessel. While stirring, gradually add 1.0 pound of TIM-BOR Professional for each gallon of treating solution required. Add remaining water to the solution and stir until the entire product has dissolved.

**15% TIM-BOR Professional Liquid Solution:** Prepare solution as above, but gradually add 1.5 lbs of TIM-BOR Professional for each gallon of treatment solution needed. Use this solution as soon as possible and do not store for an extended length of time.

15% TIM-BOR Professional Foam: Prepare a 15% liquid solution as described above and also add a surfactant-foaming agent. Generally 1-2 ounces of a foaming agent, added to the 15% liquid solution, produces a dry foam with the desired expansion ratio of approximately 20 to 1 (20 gallons of foam per 1 gallon of liquid solution). The TIM-BOR Professional foam should be of a "dry" consistency that adheres to wood surfaces so that run-off is minimized. A "wet" foam may damage wallboard or other building components. Refer to the individual foam equipment manufacturer's manual and the surfactant's label for specific instructions.

Wash and rinse all equipment after each use.

#### **Application Instructions**

**TIM-BOR Professional as a liquid solution:** TIM-BOR Professional liquid applications may be made to wood structures including decks, fences, steps, sheds, barns and other outbuildings. Application may also be made by drilling and then injecting the solution under pressure into sound wood or into the insect galleries of infested wood. TIM-BOR Professional may be applied as a foam to wood surfaces or injected into wall voids or insect galleries.

#### **Remedial and Preventative Treatment**

TIM-BOR Professional Solutions for the Control of Wood Destroying Organisms and to Kill Active Infestations of Termites, Powderpost Beetles and Wood Fungi: For remedial control of wood attacking organisms or for the protection of wood against future infestations, two applications of a 10% liquid solution are required. One application of a 15% liquid solution may be used. Apply TIM-BOR Professional solutions by brush or spray at the rate of 5 gallons of liquid solution per 1000 square feet of wood surface area. Thoroughly wet wood surface area. Application may also be made by drilling and then injecting the liquid solution under pressure into sound wood or until run-off is observed coming from entry/exit holes of infested wood.

TIM-BOR Professional Powder to Kill and Control Wood Destroying Organisms, Such as Termites and Carpenter Ants: Apply TIM-BOR Professional as is to wood members by drilling and injecting the powder into galleries or by dusting generously on wood surfaces. TIM-BOR Professional powder can also be injected or dusted into wall voids such as between studs, block voids, box sills, eaves, attics, soffits, etc. Apply TIM-BOR Professional powder to these areas at the rate of 0.5 ounce (12-14 grams) per square foot.

TIM-BOR Professional Foam: In wall voids, inject enough dry foam to contact wood surfaces of studs in the wall or the entire desired target area. Apply foam, where possible, to abutting wood surfaces and between wood joints. Apply the foam so that all accessible wood surfaces are covered with foam. TIM-BOR Professional foam can also be injected into insect galleries until run-off is observed.

#### STORAGE AND DISPOSAL

Do not contaminate water, food or feedby storage or disposal. **Pesticide Storage:** Store in a dry place. Do not store where children or animals may gain access. **Pesticide Disposal:** Wastes resulting from the use of the product may be disposed of on site or at an approved waste disposal facility. **Container Handling:** Non-refillable container; do not reuse or refill this container. Completely empty container by shaking and tapping sides and bottom to loosen clinging particles. Empty residue into application equipment; then offer for recycling, if available; or dispose of in a sanitary landfill; or, if allowed by state and local authorities, by incineration.

#### WARRANTY DISCLAIMER

To the extent not prohibited by applicable law, Manufacturer warrants that this product conforms to the chemical description on the label and is reasonably fit for the purposes stated on the label when used in strict accordance with the directions, subject to the inherent risks set forth below. To the extent not prohibited by applicable law, MANUFACTURER MAKES NO OTHER EXPRESS OR IMPLIED WARRANTY OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE OR ANY OTHER EXPRESS OR IMPLIED WARRANTY.

#### Inherent Risks of Use

The directions for use are believed to be adequate and must be carefully followed. It is impossible to eliminate all risks associated with use of this product. Lack of performance or other unintended consequences may result because of such factors as use of the product contrary to label instructions, abnormal conditions, the presence of other materials, climatic conditions or the manner of application, all of which are beyond the control of the Manufacturer. To the extent not prohibited by applicable law, the buyer/user assumes all such risks.

#### Limitation of Remedies

To the extent not prohibited by applicable law the exclusive remedy for losses or damages resulting from this product (including claims based on contract, negligence, strict liability or other legal theories) shall be limited to, at Manufacturer's election, one of the following:

- 1. Refund of purchase price paid by buyer or user for product bought, or
- 2. Replacement of amount of product used.

To the extent not prohibited by applicable law: a) Manufacturer shall not be liable for losses or damages resulting from handling or use of this product unless Manufacturer is promptly notified of such loss or damage in writing; and b) TO THE EXTENT NOT PROHIBITED BY APPLICABLE LAW IN NO CASE SHALL MANUFACTURER BE LIABLE FOR CONSEQUENTIAL OR INCIDENTAL DAMAGES OR LOSSES, INCLUDING WITHOUT LIMIT, HEALTH RELATED DAMAGES OR INJURIES.

The terms of this **Warranty Disclaimer** and **Limitation of Remedies** cannot be varied by any written or verbal statements or agreements. No employee or sales agent of Manufacturer or the seller is authorized to vary or exceed the terms of this **Warranty Disclaimer** or **Limitation of Remedies** in any manner.

It is not intended that this product be used to practice any applicable patent, whether mentioned or not, without procurement of a license, if necessary, from the owner, following investigation by the user.



100 Nisus Drive Rockford, TN USA 37853 (800) 264-0870

\*TIM-BOR and the House Design trademark are registered trademarks of U.S. Borax Inc. and are used under license. Nisus Corporation is a registered trademark of Nisus Corporation. ©2021 Nisus Corporation #TB25-PL-INT-LET-1021-SAL053119

Made in the U.S.A.