ASHLAND	Page: 1
SAFETY DATA SHEET	Revision Date: 06/02/2015
	Print Date: 3/11/2016
	SDS Number: 000000207597
Valvoline™ IMPORT MULTI-VEHICLE AUTOMATIC TRANSMISSION FLUID	Version: 1.3
820681	

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Valvoline™ IMPORT MULTI-VEHICLE

AUTOMATIC TRANSMISSION FLUID

Recommended use of the chemical and restrictions on use

Details of the supplier of the safety data	Emergency telephone number
sheet	1-800-ASHLAND (1-800-274-5263)
Ashland	
P.O. Box 2219	Regulatory Information Number
Columbus, OH 43216	1-800-325-3751
United States of America	
	Product Information
	614-790-3333
EHS Customer Requests@ashland.com	
·	

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

GHS Label element

This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Chemical nature : Defatter

Hazardous components

Chemical Name	CAS-No.	Classification	Concentration (%)
HYDROTREATED LIGHT PARAFFINIC DISTILLATE		Not a hazardous substance or mixture.	25.69
TARON TIMO BIOTILEATE		odbotanoo or mixturo.	

ASHLAND	Page: 2
SAFETY DATA SHEET	Revision Date: 06/02/2015
	Print Date: 3/11/2016
	SDS Number: 000000207597
Valvoline™ IMPORT MULTI-VEHICLE AUTOMATIC TRANSMISSION FLUID	Version: 1.3
820681	

LUBRICATING OILS, PETROLEUM, C15-30, HYDROTREATED	72623-86-0	Asp. Tox. 1; H304	2.39

SECTION 4. FIRST AID MEASURES

General advice : No hazards which require special first aid measures.

If inhaled : If breathed in, move person into fresh air.

If unconscious place in recovery position and seek medical

advice.

If symptoms persist, call a physician.

In case of skin contact : First aid is not normally required. However, it is

recommended that exposed areas be cleaned by washing

with soap and water.

In case of eye contact : Remove contact lenses.

Protect unharmed eye.

If swallowed : Do not give milk or alcoholic beverages.

Never give anything by mouth to an unconscious person.

If symptoms persist, call a physician.

Most important symptoms and effects, both acute and

delayed

: Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary

abnormalities.

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through

the skin may include:

stomach or intestinal upset (nausea, vomiting, diarrhea)

irritation (nose, throat, airways)

Notes to physician : No hazards which require special first aid measures.

ASHLAND	Page: 3
SAFETY DATA SHEET	Revision Date: 06/02/2015
	Print Date: 3/11/2016
	SDS Number: 000000207597
Valvoline™ IMPORT MULTI-VEHICLE AUTOMATIC TRANSMISSION FLUID	Version: 1.3
820681	

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local

circumstances and the surrounding environment.

Water spray Foam

Carbon dioxide (CO2)

Dry chemical

Specific hazards during

firefighting

: Do not allow run-off from fire fighting to enter drains or water

courses.

Hazardous combustion

products

: carbon dioxide and carbon monoxide

Hydrocarbons

Specific extinguishing

methods

: Product is compatible with standard fire-fighting agents.

Further information : Fire residues and contaminated fire extinguishing water must

be disposed of in accordance with local regulations.

Special protective equipment

for firefighters

: In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Persons not wearing protective equipment should be excluded

from area of spill until clean-up has been completed.

Environmental precautions : Prevent product from entering drains.

Prevent further leakage or spillage if safe to do so.

If the product contaminates rivers and lakes or drains inform

respective authorities.

Methods and materials for containment and cleaning up

: Soak up with inert absorbent material (e.g. sand, silica gel,

acid binder, universal binder, sawdust).

Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Container hazardous when empty.

Smoking, eating and drinking should be prohibited in the

application area.

ASHLAND	Page: 4
SAFETY DATA SHEET	Revision Date: 06/02/2015
	Print Date: 3/11/2016
	SDS Number: 000000207597
Valvoline™ IMPORT MULTI-VEHICLE AUTOMATIC TRANSMISSION FLUID	Version: 1.3
820681	

For personal protection see section 8.

Conditions for safe storage : Containers which are opened must be carefully resealed and

kept upright to prevent leakage.

Electrical installations / working materials must comply with

the technological safety standards.

Materials to avoid : No materials to be especially mentioned.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components with workplace control parameters				
Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	REL	5 mg/m3 Mist.	NIOSH/GUID E
		STEL	10 mg/m3 Mist.	NIOSH/GUID E
		PEL	5 mg/m3 Mist.	OSHA_TRA NS

Engineering measures : General room ventilation should be adequate for normal

conditions of use. However, if unusual operating conditions exist, provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known,

suspected or apparent adverse effects.

Personal protective equipment

Respiratory protection : No personal respiratory protective equipment normally

required.

Eye protection : Not required under normal conditions of use. Wear splash-

proof safety goggles if material could be misted or splashed

into eyes.

Skin and body protection : Wear as appropriate:

Safety shoes

Wear resistant gloves (consult your safety equipment

supplier).

Hygiene measures : General industrial hygiene practice.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

ASHLAND	Page: 5
SAFETY DATA SHEET	Revision Date: 06/02/2015
	Print Date: 3/11/2016
	SDS Number: 000000207597
Valvoline™ IMPORT MULTI-VEHICLE AUTOMATIC TRANSMISSION FLUID	Version: 1.3
820681	

Physical state : liquid

Odour : No data available

Odour Threshold : No data available

pH : No data available

Melting point/freezing point : No data available

Boiling point/boiling range : 662 °F / 350 °C

(1,013.333333 hPa)

Calculated Phase Transition Liquid/Gas

Flash point : $> 390 \, ^{\circ}\text{F} \, / > 199 \, ^{\circ}\text{C}$

Method: Cleveland open cup

Evaporation rate : No data available

Flammability (solid, gas) : No data available

Upper explosion limit : 6 %(V)

GLP: Calculated Explosive Limit

Lower explosion limit : 1 %(V)

GLP: Calculated Explosive Limit

Vapour pressure : 0.1333333 hPa (20 °C)

Calculated Vapor Pressure

Relative vapour density : No data available

Relative density : No data available

Density : 0.849 g/cm3

Solubility(ies)

Water solubility : No data available

Solubility in other solvents : No data available

Partition coefficient: n-

octanol/water

: No data available

Thermal decomposition : No data available

Viscosity

Viscosity, dynamic : No data available

Viscosity, kinematic : 36 mm2/s (40 °C)

7 mm2/s (100 °C)

ASHLAND	Page: 6
SAFETY DATA SHEET	Revision Date: 06/02/2015
	Print Date: 3/11/2016
	SDS Number: 000000207597
Valvoline™ IMPORT MULTI-VEHICLE AUTOMATIC TRANSMISSION FLUID	Version: 1.3
820681	

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous

reactions

: Product will not undergo hazardous polymerization.

Conditions to avoid : excessive heat

Incompatible materials : Strong oxidizing agents

Hazardous decomposition

products carbon dioxide and carbon monoxide

Hydrocarbons

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of : Inhalation

exposure Skin contact

Eye Contact Ingestion

Acute toxicity

Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C15-30, HYDROTREATED: Acute oral toxicity : LD 50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l

Exposure time: 4 h

Test atmosphere: dust/mist

Assessment: Not classified as acutely toxic by inhalation

under GHS.

Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD 50 (Rabbit): > 5,000 mg/kg

Remarks: No mortality observed at this dose.

Skin corrosion/irritation

Not classified based on available information.

Product:

Result: Repeated exposure may cause skin dryness or cracking.

ASHLAND	Page: 7
SAFETY DATA SHEET	Revision Date: 06/02/2015
	Print Date: 3/11/2016
	SDS Number: 000000207597
Valvoline™ IMPORT MULTI-VEHICLE AUTOMATIC TRANSMISSION FLUID	Version: 1.3
820681	

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result: Mildly irritating to skin

LUBRICATING OILS, PETROLEUM, C15-30, HYDROTREATED:

Species: Rabbit

Result: Not irritating to skin

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Result: Mildly irritating to eyes

LUBRICATING OILS, PETROLEUM, C15-30, HYDROTREATED:

Species: Rabbit

Result: Not irritating to eyes

Respiratory or skin sensitisation

Skin sensitisation: Not classified based on available information.

Respiratory sensitisation: Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C15-30, HYDROTREATED:

Test Type: Buehler Test Species: Guinea pig

Assessment: Does not cause skin sensitisation.

Germ cell mutagenicity

Not classified based on available information.

Carcinogenicity

Not classified based on available information.

Reproductive toxicity

Not classified based on available information.

STOT - single exposure

Not classified based on available information.

STOT - repeated exposure

Not classified based on available information.

Aspiration toxicity

Not classified based on available information.

Components:

LUBRICATING OILS, PETROLEUM, C15-30, HYDROTREATED:

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

May be fatal if swallowed and enters airways.

Further information

Product:

Remarks: No data available

ASHLAND	Page: 8
SAFETY DATA SHEET	Revision Date: 06/02/2015
	Print Date: 3/11/2016
	SDS Number: 000000207597
Valvoline™ IMPORT MULTI-VEHICLE AUTOMATIC TRANSMISSION FLUID	Version: 1.3
820681	

Carcinogenicity:

IARC No component of this product present at levels greater than or

equal to 0.1% is identified as probable, possible or confirmed

human carcinogen by IARC.

OSHA No component of this product present at levels greater than or

equal to 0.1% is identified as a carcinogen or potential

carcinogen by OSHA.

NTP No component of this product present at levels greater than or

equal to 0.1% is identified as a known or anticipated carcinogen

by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

LUBRICATING OILS, PETROLEUM, C15-30, HYDROTREATED:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l

Exposure time: 96 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 203

Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other

aquatic invertebrates

: EL50 (Daphnia magna (Water flea)): > 10,000 mg/l

Exposure time: 48 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 202

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >=

100 mg/l

End point: Growth inhibition

Exposure time: 72 h Test Type: static test Test substance: WAF

Method: OECD Test Guideline 201

Toxicity to fish (Chronic

toxicity)

: NOELR (Oncorhynchus mykiss (rainbow trout)): Calculated >=

1,000 mg/l

Exposure time: 14 d

Toxicity to daphnia and other

aquatic invertebrates (Chronic toxicity)

: NOEL (Daphnia (water flea)): 10 mg/l

Exposure time: 21 d Test substance: WAF

Method: OECD Test Guideline 211

ASHLAND	Page: 9
SAFETY DATA SHEET	Revision Date: 06/02/2015
	Print Date: 3/11/2016
	SDS Number: 000000207597
Valvoline™ IMPORT MULTI-VEHICLE AUTOMATIC TRANSMISSION FLUID	Version: 1.3
820681	

Persistence and degradability

LUBRICATING OILS, PETROLEUM, C15-30, HYDROTREATED:

Biodegradability : Result: Not readily biodegradable.

Biodegradation: 2 - 4 % Exposure time: 28 d

Method: OECD Test Guideline 301B

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

Product:

Additional ecological

information

: An environmental hazard cannot be excluded in the event of unprofessional handling or disposal., Toxic to aquatic life with

long lasting effects.

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : The product should not be allowed to enter drains, water

courses or the soil.

Dispose of in accordance with all applicable local, state and

federal regulations.

Contaminated packaging : Empty remaining contents.

Dispose of as unused product.

Empty containers should be taken to an approved waste

handling site for recycling or disposal.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD	SUBSIDIARY	PACKING	MARINE
		CLASS	HAZARDS	GROUP	POLLUTANT /
					LTD. QTY.

MEXICAN REGULATION FOR THE LAND TRANSPORT OF HAZARDOUS MATERIALS AND WASTES

UN	3082	Not dangerous goods	9	

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

ASH	ILAI				Page: 10
SAFETY DAT	A SHEET			Revi	sion Date: 06/02/2015
<u> </u>	7. 011221				Print Date: 3/11/2016
V I I TM IMPOR	T. M. II. T. I. V. E. II. O. I.	E ALITONATIO		SDS N	umber: 000000207597
Valvoline™ IMPOR TRANSMISSION F		E AUTOMATIC			Version: 1.3
	LOID				
820681					
UN 3082 N	Not dangerous god	ods 9			
NTERNATIONAL A	IR TRANSPORT	ASSOCIATION - CAR	GO		
UN 3082 N	Not dangerous god	ods 9			
NTERNATIONAL M	ARITIME DANGE	EROUS GOODS			
UN 3082 N	Not dangerous god	ods 9			
RANSPORT CANA	ADA - INLAND W	ATERWAYS			
١	Not dangerous god	ods			
RANSPORT CANA	ADA - RAIL				
١	Not dangerous goo	ods			
RANSPORT CANA	ADA - ROAD				
	ENVIRONMENTAL			Ш	MARINE
	HAZARDOUS SUE LIQUID, N.O.S.	3STANCE,			POLLUTANT:(HETEROCYCL
_					IC
					ETHER)LIMIT
					ED QUANTITY
J.S. DOT - INLAND				111	
	Environmentally ha substance, liquid, r			III	
J.S. DOT - RAIL					
	Environmentally ha	azardous		III	
	substance, liquid, r				
J.S. DOT - ROAD					
	SUSTANCIA LIQU			III	
<u> </u>	POTENCIALMENT	ΓΕ		III	
S F F	POTENCIALMENT PELIGROSAS PAI	ΓΕ RA EL		III	
S F F	POTENCIALMENT	ΓΕ RA EL		III	
S F F	POTENCIALMENT PELIGROSAS PAI MEDIO AMBIENTE	re RA EL <u>E, N.E.P.</u>		III	
F F N	POTENCIALMENT PELIGROSAS PAI MEDIO AMBIENTE BL = COMBUSTIB	re RA EL <u>E, N.E.P.</u>		III	

ASHLAND	Page: 11
SAFETY DATA SHEET	Revision Date: 06/02/2015
	Print Date: 3/11/2016
	SDS Number: 000000207597
Valvoline™ IMPORT MULTI-VEHICLE AUTOMATIC TRANSMISSION FLUID	Version: 1.3
820681	

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

SARA 311/312 Hazards : No SARA Hazards

SARA 313 : This material does not contain any chemical components with

Component(s)SARA 313 known CAS numbers that exceed the threshold (De Minimis)

reporting levels established by SARA Title III, Section 313.

Pennsylvania Right To Know

HYDROTREATED HEAVY PARAFFINIC 64742-54-7 50.00 - 70.00 %

BASE OIL

HYDROTREATED LIGHT PARAFFINIC 64742-55-8 20.00 - 30.00 %

DISTILLATE

LUBRICANT ADDITIVE Not Assigned 10.00 - 20.00 %

New Jersey Right To Know

HYDROTREATED HEAVY PARAFFINIC 64742-54-7 50.00 - 70.00 %

BASE OIL

HYDROTREATED LIGHT PARAFFINIC 64742-55-8 20.00 - 30.00 %

DISTILLATE

LUBRICANT ADDITIVE Not Assigned 10.00 - 20.00 %

LUBRICATING OILS, PETROLEUM, C15- 72623-86-0 1.00 - 5.00 %

30, HYDROTREATED

California Prop 65 Proposition 65 warnings are not required for this product

based on the results of a risk assessment.

The components of this product are reported in the following inventories:

TSCA : On TSCA Inventory

DSL : All components of this product are on the Canadian DSL.

AUSTR : On the inventory, or in compliance with the inventory

ENCS : On the inventory, or in compliance with the inventory

KECL : On the inventory, or in compliance with the inventory

PICCS : On the inventory, or in compliance with the inventory

ASHLAND	Page: 12
SAFETY DATA SHEET	Revision Date: 06/02/2015
	Print Date: 3/11/2016
	SDS Number: 000000207597
Valvoline™ IMPORT MULTI-VEHICLE AUTOMATIC TRANSMISSION FLUID	Version: 1.3
820681	

IECSC : On the inventory, or in compliance with the inventory


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information

Revision Date: 06/02/2015



NFPA Flammable and Combustible Liquids Classification

Combustible Liquid Class IIIB

Full text of H-Statements referred to under sections 2 and 3.

H303 May be harmful if swallowed.

H304 May be fatal if swallowed and enters airways.

Further information

Sources of key data used to compile the Safety Data Sheet
Ashland internal data including own and sponsored test reports
The UNECE administers regional agreements implementing harmonised classification for labelling

(GHS) and transport.

The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Ashland's Environmental Health and Safety Department (1-800-325-3751).

ASHLAND	Page: 13
SAFETY DATA SHEET	Revision Date: 06/02/2015
	Print Date: 3/11/2016
	SDS Number: 000000207597
Valvoline™ IMPORT MULTI-VEHICLE AUTOMATIC TRANSMISSION FLUID	Version: 1.3
820681	

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet:

ACGIH: American Conference of Industrial Hygienists

BEI : Biological Exposure Index

CAS: Chemical Abstracts Service (Division of the American Chemical Society).

CMR: Carcinogenic, Mutagenic or Toxic for Reproduction

FG: Food grade

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

H-statement: Hazard Statement

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization

ICAO-TI (ICAO): Technical Instructions by the "International Civil Aviation Organization"

IMDG: International Maritime Code for Dangerous Goods

ISO: International Organization for Standardization

logPow: octanol-water partition coefficient

LCxx: Lethal Concentration, for xx percent of test population

LDxx: Lethal Dose, for xx percent of test population. ICxx: Inhibitory Concentration for xx of a substance

Ecxx : Effective Concentration of xx N.O.S.: Not Otherwise Specified

OECD: Organization for Economic Co-operation and Development

OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic

PPE: Personal Protective Equipment STEL: Short-term exposure limit STOT: Specific Target Organ Toxicity

TLV: Threshold Limit Value TWA: Time-weighted average

vPvB: Very Persistent and Very Bioaccumulative

WEL: Workplace Exposure Level

CERCLA: Comprehensive Environmental Response, Compensation, and Liability Act

DOT: Department of Transportation

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act HMIRC : Hazardous Materials Information Review Commission

HMIS: Hazardous Materials Identification System NFPA: National Fire Protection Association

NIOSH: National Institute for Occupational Safety and Health OSHA: Occupational Safety and Health Administration

PMRA: Health Canada Pest Management Regulatory Agency

RTK: Right to Know

WHMIS: Workplace Hazardous Materials Information System