		Page: 1
SAFETY DATA SHEET		Revision Date: 10/25/2017
		Print Date: 1/3/2018
		SDS Number: 000000149117
Valvoline™ CVT Full Synthetic Continuously Variable Transmission Fluid		Version: 1.5
804751		

29 CFR 1910.1200 (OSHA HazCom 2012)

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product identifier

Trade name : Valvoline™ CVT Full Synthetic Continuously Variable Transmission Fluid


<p>Details of the supplier of the safety data sheet Valvoline LLC 100 Valvoline Way Lexington, KY 40509 United States of America (USA) 1-800-TEAMVAL (1-800-8326-825)</p>	<p>Emergency telephone number 1-800-VALVOLINE (1-800-825-8654)</p> <p>Regulatory Information Number 1-800-TEAMVAL (1-800-8326-825)</p> <p>Product Information 1-800-TEAMVAL (1-800-8326-825)</p>
---	--

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Skin sensitization : Category 1

GHS label elements

Hazard pictograms : 

Signal Word : Warning

Hazard Statements : May cause an allergic skin reaction.

Precautionary Statements : **Prevention:**
Avoid breathing dust/ fume/ gas/ mist/ vapors/ spray.
Contaminated work clothing must not be allowed out of the workplace.
Wear protective gloves.
Response:
IF ON SKIN: Wash with plenty of soap and water.
If skin irritation or rash occurs: Get medical advice/ attention.
Wash contaminated clothing before reuse.
Disposal:
Dispose of contents/ container to an approved waste disposal

SAFETY DATA SHEET

Revision Date: 10/25/2017

Print Date: 1/3/2018

SDS Number: 000000149117

Valvoline™ CVT Full Synthetic Continuously Variable Transmission Fluid

Version: 1.5

804751

plant.

Other hazards

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Hazardous components

Chemical name	CAS-No.	Classification	Concentration (%)
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	This material is not considered hazardous under the OSHA Hazard Communication Standard (HazCom 2012).	67.0534
Acetamide, 2-hydroxy-, N,N-dicoco alkyl derivs.	866259-61-2	Skin Sens. 1; H317	0.999
C14-C18 alpha-olefin epoxide, reaction products with boric acid		Skin Sens. 1; H317	0.1189

SECTION 4. FIRST AID MEASURES

- General advice : Move out of dangerous area.
Show this safety data sheet to the doctor in attendance.
Do not leave the victim unattended.
- If inhaled : If breathed in, move person into fresh air.
If unconscious, place in recovery position and seek medical advice.
If symptoms persist, call a physician.
- In case of skin contact : Remove contaminated clothing. If irritation develops, get medical attention.
If on skin, rinse well with water.
First aid is not normally required. However, it is recommended that exposed areas be cleaned by washing with soap and water.
Wash contaminated clothing before re-use.
- In case of eye contact : Flush eyes with water as a precaution.
Remove contact lenses.



SAFETY DATA SHEET		Revision Date: 10/25/2017
		Print Date: 1/3/2018
		SDS Number: 000000149117
Valvoline™ CVT Full Synthetic Continuously Variable Transmission Fluid		Version: 1.5
804751		

Protect unharmed eye.
If eye irritation persists, consult a specialist.

If swallowed : Do not give milk or alcoholic beverages.
Never give anything by mouth to an unconscious person.
If symptoms persist, call a physician.

Most important symptoms and effects, both acute and delayed : Acute aspiration of large amounts of oil-laden material may produce a serious aspiration pneumonia. Patients who aspirate these oils should be followed for the development of long-term sequelae. Repeated aspiration of small quantities of mineral oil can produce chronic inflammation of the lungs (i.e. lipoid pneumonia) that may progress to pulmonary fibrosis. Symptoms are often subtle and radiological changes appear worse than clinical abnormalities. Occasionally, persistent cough, irritation of the upper respiratory tract, shortness of breath with exertion, fever, and bloody sputum occur. Inhalation exposure to oil mists below current workplace exposure limits is unlikely to cause pulmonary abnormalities.

Signs and symptoms of exposure to this material through breathing, swallowing, and/or passage of the material through the skin may include:
stomach or intestinal upset (nausea, vomiting, diarrhea)
irritation (nose, throat, airways)
May cause an allergic skin reaction.

Notes to physician : No hazards which require special first aid measures.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Water spray
Foam
Carbon dioxide (CO2)
Dry chemical

Unsuitable extinguishing media : High volume water jet

Specific hazards during firefighting : Do not allow run-off from fire fighting to enter drains or water courses.

Hazardous combustion products : carbon dioxide and carbon monoxide
Hydrocarbons

**SAFETY DATA SHEET**

Revision Date: 10/25/2017

Print Date: 1/3/2018

SDS Number: 000000149117

Valvoline™ CVT Full Synthetic Continuously Variable
Transmission Fluid

Version: 1.5

804751

Specific extinguishing methods : Product is compatible with standard fire-fighting agents.

Product is compatible with standard fire-fighting agents.

Further information : Standard procedure for chemical fires.

Standard procedure for chemical fires.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Use personal protective equipment.
Persons not wearing protective equipment should be excluded from area of spill until clean-up has been completed.

Environmental precautions : Prevent product from entering drains.
Prevent further leakage or spillage if safe to do so.

Methods and materials for containment and cleaning up : Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust).
Keep in suitable, closed containers for disposal.

Other information : Comply with all applicable federal, state, and local regulations.

SECTION 7. HANDLING AND STORAGE

Advice on safe handling : Do not breathe vapours/dust.
Do not smoke.
Persons susceptible to skin sensitisation problems or asthma, allergies, chronic or recurrent respiratory disease should not be employed in any process in which this mixture is being used.
Container hazardous when empty.
Avoid exposure - obtain special instructions before use.
Avoid contact with skin and eyes.
Smoking, eating and drinking should be prohibited in the application area.
For personal protection see section 8.
Dispose of rinse water in accordance with local and national regulations.

Conditions for safe storage : Keep container tightly closed in a dry and well-ventilated

SAFETY DATA SHEET

Revision Date: 10/25/2017

Print Date: 1/3/2018

SDS Number: 000000149117

Valvoline™ CVT Full Synthetic Continuously Variable Transmission Fluid

Version: 1.5

804751

place.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
HYDROTREATED LIGHT PARAFFINIC DISTILLATE	64742-55-8	TWA	5 mg/m3 Mist	OSHA Z-1
		TWA	5 mg/m3 Inhalable fraction	ACGIH
		TWA	5 mg/m3 Mist	OSHA P0
		TWA	5 mg/m3 Mist	NIOSH REL
		ST	10 mg/m3 Mist	NIOSH REL
		PEL	5 mg/m3 particulate	CAL PEL

Hazardous components without workplace control parameters

Components	CAS-No.
Acetamide, 2-hydroxy-, N,N-dicoco alkyl derivs.	866259-61-2
C14-C18 alpha-olefin epoxide, reaction products with boric acid	

Engineering measures : Provide sufficient mechanical (general and/or local exhaust) ventilation to maintain exposure below exposure guidelines (if applicable) or below levels that cause known, suspected or apparent adverse effects.

Personal protective equipment

Hand protection

Remarks : The suitability for a specific workplace should be discussed with the producers of the protective gloves.

Eye protection : Not required under normal conditions of use. Wear splash-proof safety goggles if material could be misted or splashed into eyes.

Skin and body protection : Wear as appropriate:
Impervious clothing
Safety shoes

**SAFETY DATA SHEET**

Revision Date: 10/25/2017

Print Date: 1/3/2018

SDS Number: 000000149117

Valvoline™ CVT Full Synthetic Continuously Variable
Transmission Fluid

Version: 1.5

804751

Choose body protection according to the amount and concentration of the dangerous substance at the work place. Discard gloves that show tears, pinholes, or signs of wear. Wear resistant gloves (consult your safety equipment supplier).

Hygiene measures : Wash hands before breaks and at the end of workday.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Physical state	: liquid
Colour	: clear
Odour	: characteristic
Odour Threshold	: No data available
pH	: Not applicable
Melting point/freezing point	: No data available
Boiling point/boiling range	: No data available
Flash point	: > 219.99 °F / > 104.44 °C Calculated Flash Point
Evaporation rate	: No data available
Flammability (solid, gas)	: No data available
Upper explosion limit	: No data available
Lower explosion limit	: No data available
Vapour pressure	: No data available No data available
Relative vapour density	: No data available
Relative density	: No data available
Density	: 0.8436 g/cm ³ (25 °C)
Solubility(ies) Water solubility	: immiscible

**SAFETY DATA SHEET**

Revision Date: 10/25/2017

Print Date: 1/3/2018

SDS Number: 000000149117

Valvoline™ CVT Full Synthetic Continuously Variable
Transmission Fluid

Version: 1.5

804751

Solubility in other solvents : No data available

Partition coefficient: n-
octanol/water : No data available

Thermal decomposition : No data available

Viscosity
Viscosity, dynamic : No data available

Viscosity, kinematic : 33.9 mm²/s (40 °C)

Oxidizing properties : No data available

SECTION 10. STABILITY AND REACTIVITY

Reactivity : No decomposition if stored and applied as directed.

Chemical stability : Stable under recommended storage conditions.

Possibility of hazardous
reactions : Product will not undergo hazardous polymerization.

Conditions to avoid : excessive heat

Incompatible materials : Strong oxidizing agents

Hazardous decomposition
products : carbon dioxide and carbon monoxide
Hydrocarbons

SECTION 11. TOXICOLOGICAL INFORMATION

Information on likely routes of
exposure : Inhalation
Skin contact
Eye Contact
Ingestion

Acute toxicity

Not classified based on available information.

Components:**HYDROTREATED LIGHT PARAFFINIC DISTILLATE:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.58 mg/l
Exposure time: 4 h

**SAFETY DATA SHEET**

Revision Date: 10/25/2017

Print Date: 1/3/2018

SDS Number: 000000149117

Valvoline™ CVT Full Synthetic Continuously Variable Transmission Fluid

Version: 1.5

804751

Test atmosphere: dust/mist
Assessment: Not classified as acutely toxic by inhalation under GHS.

Remarks: No mortality observed at this dose.

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg
Remarks: No mortality observed at this dose.

Skin corrosion/irritation

Not classified based on available information.

Product:

Remarks: May cause skin irritation in susceptible persons.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Species: Rabbit

Result: No skin irritation

C14-C18 alpha-olefin epoxide, reaction products with boric acid:

Result: No skin irritation

Serious eye damage/eye irritation

Not classified based on available information.

Product:

Remarks: Unlikely to cause eye irritation or injury.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Species: Rabbit

Result: No eye irritation

C14-C18 alpha-olefin epoxide, reaction products with boric acid:

Result: No eye irritation

Respiratory or skin sensitisation

Skin sensitisation: May cause an allergic skin reaction.

Respiratory sensitisation: Not classified based on available information.

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Test Type: Buehler Test

Species: Guinea pig


Assessment: Does not cause skin sensitisation.

Acetamide, 2-hydroxy-, N,N-dicoco alkyl derivs.:

Assessment: May cause sensitisation by skin contact.

Result: May cause sensitisation by skin contact.

C14-C18 alpha-olefin epoxide, reaction products with boric acid:

		Page: 9
SAFETY DATA SHEET		Revision Date: 10/25/2017
		Print Date: 1/3/2018
		SDS Number: 000000149117
Valvoline™ CVT Full Synthetic Continuously Variable Transmission Fluid 804751		Version: 1.5

Assessment: May cause sensitisation by skin contact.

Germ cell mutagenicity
Not classified based on available information.

Carcinogenicity
Not classified based on available information.

Reproductive toxicity
Not classified based on available information.

STOT - single exposure
Not classified based on available information.

STOT - repeated exposure
Not classified based on available information.

Aspiration toxicity
Not classified based on available information.

Product:
No aspiration toxicity classification

Components:
HYDROTREATED LIGHT PARAFFINIC DISTILLATE:
May be fatal if swallowed and enters airways.

Further information
Product:
Remarks: No data available

Carcinogenicity:
IARC No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

OSHA No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

NTP No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity
Product:
Ecotoxicology Assessment
Acute aquatic toxicity : Not classified based on available information.
Chronic aquatic toxicity : Not classified based on available information.

Components:

SAFETY DATA SHEET

Revision Date: 10/25/2017

Print Date: 1/3/2018

SDS Number: 000000149117

Valvoline™ CVT Full Synthetic Continuously Variable Transmission Fluid

Version: 1.5

804751

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): > 100 mg/l
 Exposure time: 96 h
 Test Type: static test
 Test substance: WAF
 Method: OECD Test Guideline 203
 Remarks: No toxicity at the limit of solubility

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 10,000 mg/l
 Exposure time: 48 h
 Test Type: static test
 Test substance: WAF
 Method: OECD Test Guideline 202

Toxicity to algae : NOEL (Pseudokirchneriella subcapitata (green algae)): >= 100 mg/l
 End point: Growth inhibition
 Exposure time: 72 h
 Test Type: static test
 Test substance: WAF
 Method: OECD Test Guideline 201

Toxicity to fish (Chronic toxicity) : NOELR (Oncorhynchus mykiss (rainbow trout)): Calculated >= 1,000 mg/l
 Exposure time: 14 d

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEL (Daphnia (water flea)): 10 mg/l
 Exposure time: 21 d
 Test substance: WAF
 Method: OECD Test Guideline 211

Persistence and degradability

Components:

HYDROTREATED LIGHT PARAFFINIC DISTILLATE:

Biodegradability : Result: Not readily biodegradable.
 Biodegradation: 2 - 4 %
 Exposure time: 28 d
 Method: OECD Test Guideline 301B

No data available

Bioaccumulative potential

Components:

No data available

Mobility in soil

Components:

No data available

Other adverse effects

No data available

Product:

Additional ecological : No data available



SAFETY DATA SHEET

Revision Date: 10/25/2017

Print Date: 1/3/2018

SDS Number: 000000149117

Valvoline™ CVT Full Synthetic Continuously Variable Transmission Fluid

Version: 1.5

804751

information

Components:

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

General advice : Do not dispose of waste into sewer.
 Do not contaminate ponds, waterways or ditches with chemical or used container.
 Send to a licensed waste management company.
 Dispose of in accordance with all applicable local, state and federal regulations.

Contaminated packaging : Empty remaining contents.
 Dispose of as unused product.
 Empty containers should be taken to an approved waste handling site for recycling or disposal.
 Do not re-use empty containers.

SECTION 14. TRANSPORT INFORMATION

International transport regulations

REGULATION

ID NUMBER	PROPER SHIPPING NAME	*HAZARD CLASS	SUBSIDIARY HAZARDS	PACKING GROUP	MARINE POLLUTANT / LTD. QTY.

MX_DG

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - PASSENGER

Not dangerous goods

INTERNATIONAL AIR TRANSPORT ASSOCIATION - CARGO

Not dangerous goods

INTERNATIONAL MARITIME DANGEROUS GOODS

Not dangerous goods

TDG_INWT_C

Not dangerous goods



SAFETY DATA SHEET

Revision Date: 10/25/2017

Print Date: 1/3/2018

SDS Number: 000000149117

Valvoline™ CVT Full Synthetic Continuously Variable Transmission Fluid

Version: 1.5

804751

TDG_RAIL_C

Not dangerous goods

TDG_ROAD_C

Not dangerous goods

U.S. DOT - INLAND WATERWAYS

Not dangerous goods

CFR_RAIL_C

Not dangerous goods

U.S. DOT - ROAD

Not dangerous goods

***ORM = ORM-D, CBL = COMBUSTIBLE LIQUID**

Marine pollutant	no
------------------	----

Dangerous goods descriptions (if indicated above) may not reflect quantity, end-use or region-specific exceptions that can be applied. Consult shipping documents for descriptions that are specific to the shipment.

SECTION 15. REGULATORY INFORMATION

**EPCRA - Emergency Planning and Community Right-to-Know Act
CERCLA Reportable Quantity**

This material does not contain any components with a CERCLA RQ.

SARA 304 Extremely Hazardous Substances Reportable Quantity

This material does not contain any components with a section 304 EHS RQ.

SARA 311/312 Hazards : Acute Health Hazard

SARA 313

This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

California Prop 65

This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm.

SAFETY DATA SHEET		Revision Date: 10/25/2017
		Print Date: 1/3/2018
		SDS Number: 000000149117
Valvoline™ CVT Full Synthetic Continuously Variable Transmission Fluid		Version: 1.5
804751		

The components of this product are reported in the following inventories:

- DSL : All components of this product are on the Canadian DSL
- AICS : On the inventory, or in compliance with the inventory
- ENCS : On the inventory, or in compliance with the inventory
- KECI : On the inventory, or in compliance with the inventory
- PICCS : On the inventory, or in compliance with the inventory
- IECSC : On the inventory, or in compliance with the inventory
- TSCA : On TSCA Inventory


Inventories

AICS (Australia), DSL (Canada), IECSC (China), REACH (European Union), ENCS (Japan), ISHL (Japan), KECI (Korea), NZIoC (New Zealand), PICCS (Philippines), TCSI (Taiwan), TSCA (USA)

SECTION 16. OTHER INFORMATION

Further information


Revision Date: 10/25/2017

<p>NFPA:</p> <div style="text-align: center;"> <p>Flammability</p>  <p>Health Instability</p> <p>Special hazard.</p> </div>	<p>HMIS III:</p> <table border="1" style="width: 100%;"> <tr> <td style="background-color: blue; color: white;">HEALTH</td> <td style="text-align: center;">2</td> </tr> <tr> <td style="background-color: red; color: white;">FLAMMABILITY</td> <td style="text-align: center;">1</td> </tr> <tr> <td style="background-color: yellow;">PHYSICAL HAZARD</td> <td style="text-align: center;">0</td> </tr> </table> <p>0 = not significant, 1 =Slight, 2 = Moderate, 3 = High 4 = Extreme, * = Chronic</p>	HEALTH	2	FLAMMABILITY	1	PHYSICAL HAZARD	0
HEALTH	2						
FLAMMABILITY	1						
PHYSICAL HAZARD	0						

NFPA Flammable and Combustible Liquids Classification
Combustible Liquid Class IIIB

Full text of H-Statements

H317 May cause an allergic skin reaction.

		Page: 14
SAFETY DATA SHEET		Revision Date: 10/25/2017
		Print Date: 1/3/2018
		SDS Number: 000000149117
Valvoline™ CVT Full Synthetic Continuously Variable Transmission Fluid		Version: 1.5
804751		

Sources of key data used to compile the Safety Data Sheet
Valvoline internal data including own and sponsored test reports
The UNECE administers regional agreements implementing harmonised classification for labelling (GHS) and transport.


The information accumulated herein is believed to be accurate but is not warranted to be whether originating with the company or not. Recipients are advised to confirm in advance of need that the information is current, applicable, and suitable to their circumstances. This SDS has been prepared by Valvoline's Environmental Health and Safety Department (1-800-VALVOLINE).

List of abbreviations and acronyms that could be, but not necessarily are, used in this safety data sheet :

ACGIH : American Conference of Industrial Hygienists
BEI : Biological Exposure Index
CAS : Chemical Abstracts Service (Division of the American Chemical Society).
CMR : Carcinogenic, Mutagenic or Toxic for Reproduction
FG : Food grade
GHS : Globally Harmonized System of Classification and Labeling of Chemicals.
H-statement : Hazard Statement
IATA : International Air Transport Association.
IATA-DGR : Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO : International Civil Aviation Organization
ICAO-TI (ICAO) : Technical Instructions by the "International Civil Aviation Organization"
IMDG : International Maritime Code for Dangerous Goods
ISO : International Organization for Standardization
logPow : octanol-water partition coefficient
LCxx : Lethal Concentration, for xx percent of test population
LDxx : Lethal Dose, for xx percent of test population.
ICxx : Inhibitory Concentration for xx of a substance
Ecxx : Effective Concentration of xx
N.O.S.: Not Otherwise Specified
OECD : Organization for Economic Co-operation and Development
OEL : Occupational Exposure Limit
P-Statement : Precautionary Statement
PBT : Persistent , Bioaccumulative and Toxic
PPE : Personal Protective Equipment
STEL : Short-term exposure limit
STOT : Specific Target Organ Toxicity
TLV : Threshold Limit Value
TWA : Time-weighted average
vPvB : Very Persistent and Very Bioaccumulative
WEL : Workplace Exposure Level

CERCLA : Comprehensive Environmental Response, Compensation, and Liability Act
DOT : Department of Transportation

	Page: 15
SAFETY DATA SHEET	Revision Date: 10/25/2017
	Print Date: 1/3/2018
	SDS Number: 000000149117
Valvoline™ CVT Full Synthetic Continuously Variable Transmission Fluid 804751	Version: 1.5

FIFRA : Federal Insecticide, Fungicide, and Rodenticide Act
HMIRC : Hazardous Materials Information Review Commission
HMIS : Hazardous Materials Identification System
NFPA : National Fire Protection Association
NIOSH : National Institute for Occupational Safety and Health
OSHA : Occupational Safety and Health Administration
PMRA : Health Canada Pest Management Regulatory Agency
RTK : Right to Know
WHMIS : Workplace Hazardous Materials Information System