

SAFETY DATA SHEET

1. IDENTIFICATION

Product Name:

VAPORPH3OS[®] Phosphine Fumigant

Phosphine gas **Product Description:** Synonyms: **Chemical Family:** Phosphine **Molecular Formula:** PH3 Molecular Weight: 34 Intended/Recommended Use: Fumigant

Phosphine, Hydrogen Phosphide

CYTEC INDUSTRIES INC., FIVE GARRET MOUNTAIN PLAZA, WOODLAND PARK, NEW JERSEY 07424, USA For Product and all Non-Emergency Information call 1-800/652-6013. Outside the USA and Canada call 1-973/357-3193.

EMERGENCY PHONE (24 hours/day) - For emergency only involving spill, leak, fire, exposure or accident call: Asia Pacific:

Australia - +61-3-9663-2130 or 1800-033-111 (IXOM) China (PRC) - +86 0532 83889090 (NRCC) New Guinea - +61-3-9663-2130 or 1800-033-111 New Zealand - +61-3-9663-2130 or 0800-734-607 (IXOM) India, Japan, Korea, Malaysia, Thailand - +65 3158 1074 (Carechem24 Singapore) India (Hindi Speaking Only) - +65 3158 1198 or 000800 100 7479 (Carechem24 Singapore) Canada: +1-905-356-8310 (Cytec Welland, Canada plant) Europe/Africa/Middle East (Carechem24 UK): Europe, Middle East, Africa, Israel - +44 (0) 1235 239 670 (Arabic speaking countries) - +44 (0) 1235 239 671 Latin America: Brazil - 0800 7077 022 (SUATRANS) Chile - +56-2-2-247-3600 (CITUC QUIMICO)

All Others - +52-376-73 74122 (Cytec Atequiza, Mexico plant)

USA: +1-703-527-3887 or 1-800-424-9300 (CHEMTREC #CCN6083)

The ® indicates a Registered Trademark in the United States and the ™ indicates a trademark in the United States. The mark may also be registered, subject of an application for registration, or a trademark in other countries.

2. HAZARDS IDENTIFICATION

GHS Classification

Flammable Gas Hazard Category 1 Gases Under Pressure - Compressed Gas Acute Toxicity (Inhalation) Hazard Category 1 Skin Corrosion / Irritation Hazard Category 1B Serious Eye Damage / Eye Irritation Hazard Category 1 Aquatic Environment Acute Hazard Category 1

LABEL ELEMENTS



Signal Word Danger

Hazard Statements

Extremely flammable gas Contains gas under pressure; may explode if heated Fatal if inhaled Causes severe skin burns and eye damage Very toxic to aquatic life

Precautionary Statements

Keep away from heat/sparks/open flames/hot surfaces. - No smoking. Do not breathe dust/fume/gas/mist/vapours/spray. Use only outdoors or in a well-ventilated area. Wear respiratory protection. Wash face, hands and any exposed skin thoroughly after handling. Wear protective gloves/protective clothing/eye protection/face protection. Avoid release to the environment. Leaking gas fire: Do not extinguish, unless leak can be stopped safely. Eliminate all ignition sources if safe to do so. IF INHALED: Remove person to fresh air and keep comfortable for breathing. Immediately call a POISON CENTER or doctor/physician. Specific treatment (see supplemental first aid instructions on this label). IF SWALLOWED: Rinse mouth. Do NOT induce vomiting. IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower. Wash contaminated clothing before reuse.

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Collect spillage.

Protect from sunlight. Store in a well-ventilated place.

Store in a well-ventilated place. Keep container tightly closed.

Store locked up.

Dispose of contents/container in accordance with local and national regulations.

Hazards Not Otherwise Classified (HNOC), Other Hazards

Phosphine gas may react with certain metals and cause corrosion, especially at higher temperatures and relative humidity.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance, Mixture or Article? Substance

HAZARDOUS INGREDIENTS

Component / CAS No.	%	GHS Classification	Carcinogen
Phosphine	97 - 99	Flam. Gas 1 (H220)	IARC 2A(as Non-arsenical
7803-51-2		Press. Gas	insecticides)
		Acute Tox. 1 (H330)	
		Skin Corr. 1B (H314)	
		Eye Dam. 1 (H318)	
		Aquatic Acute 1 (H400)	

Component / CAS No.	%	GHS Classification	Carcinogen
Hydrogen	0.2 - 1.0	Flam. Gas 1 (H220) U	-
1333-74-0		Press. Gas U	

The specific chemical identity and/or exact percentage of composition for one or more ingredients has been withheld as a trade secret.

Additional GHS classification or other information may be included in this section but has not been adopted by OSHA. See Section 16 for full text of H phrases.

4. FIRST AID MEASURES

DESCRIPTION OF FIRST AID MEASURES

Eye Contact:

Rinse immediately with plenty of water for at least 15 minutes. Obtain medical attention immediately.

Skin Contact:

Not an expected route of exposure. Gas is not known to be absorbed through skin.

Ingestion:

Not an expected route of exposure. Gas is not known to be absorbed through skin.

Inhalation:

Move person to fresh air. If person is not breathing, immediately call for emergency medical support then, begin cardiopulmonary resuscitation including artificial respiration, preferably with a bag-valve-mask device if possible. Rescuers within the areas of potentially unsafe levels of this product (the "HOT ZONE") should employ appropriate personal protective equipment such as SCBA during the rescue of the victim. Call a poison control center or doctor for further treatment advice.

MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED

None known

INDICATION OF ANY IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDS

Not applicable

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media:

Use water spray, alcohol foam, carbon dioxide or dry chemical to extinguish fires.

Extinguishing Media to Avoid:

full water jet

Protective Equipment:

Firefighters, and others exposed, wear self-contained breathing apparatus. Wear full firefighting protective clothing. See MSDS Section 8 (Exposure Controls/Personal Protection).

Special Hazards:

In case of fire, stop flow of gas if possible. Keep cylinders cool by spraying with water if exposed to fire. Cylinders are not fitted with pressure relief devices and may explode if over-heated. Move cylinders from fire area if you can do it without risk. Withdraw immediately if cylinders can not be kept cool. Damaged cylinders should be handled only by a specialist. This material is spontaneously flammable in air and may form explosive mixtures in air.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions:

Where exposure level is not known, wear approved, positive pressure, self-contained respirator. Where exposure level is known, wear approved respirator suitable for level of exposure.

Methods For Cleaning Up:

Remove sources of ignition. Evacuate area. If burning, allow to burn until leak is stopped.

References to other sections:

See Sections 8 and 13 for additional information.

7. HANDLING AND STORAGE

HANDLING

Precautions: Avoid release to the environment. Keep away from heat, sparks and open flame. - No smoking. Use only outdoors or in a well-ventilated area. Wear respiratory protection. Wash hands thoroughly after handling. Wear protective gloves/clothing and eye/face protection. Do not breathe gas.

Special Handling Statements: Before dispensing product, purge equipment with an inert gas. Cylinders must be handled in accordance with industry standards for compressed gases. Refer to the Compressed Gas Association (CGA) Pamphlet P-1 "Safe Handling of Compressed Gases In Containers". Phosphine gas may react with certain metals and cause corrosion, especially at higher temperatures and relative humidity. Metals such as brass, copper and other copper alloys and precious metals are susceptible to corrosion.

STORAGE

Cylinders should be stored in an assigned area which should be cool, dry, well ventilated and fire resistant. It is recommended that both full and used cylinders be stored outdoors in a dedicated and properly designed and labeled storage area, away from other building ventilation intakes. This area should be secured, locked and have a well-drained, firm and level surface, preferably reinforced concrete. Cylinders must be stored in an upright position and secured or protected from falling. Cylinders should never be stored where the temperatures will exceed 60 C (140 F). The indoor storage of toxic gases is prohibited in some jurisdictions. The storage of these gases in occupied spaces is not recommended. Indoor storage in a separate building with no other occupancy is suitable. The building should be adequately ventilated and equipped with a continuous monitoring and alarm system.

Storage Temperature: Store at <60 °C 140 °F **Reason:** Safety.

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering Measures:

Utilize a closed system process where feasible. Where this material is not used in a closed system, good enclosure and local exhaust ventilation should be provided to control exposure.

Respiratory Protection:

In case of insufficient ventilation, wear suitable respiratory equipment. If exposed to vapour or spray, wear self-contained breathing apparatus. Continuously monitoring phosphine concentration in the workplace is recommended. Emergency procedure should be established for phosphine leaks.

Eye Protection:

Wear eye/face protection. Provide eye wash fountain and safety shower in close proximity to points of potential exposure.

Skin Protection:

Not an expected route of exposure. Gas is not known to be absorbed through skin. Steel toed safety shoes are recommended for anyone handling compressed gas cylinders.

Hand Protection:

Wear impermeable gloves. Replace gloves immediately when torn or any change in appearance (dimension, colour, flexibility etc) is noticed.

Additional Advice:

Food, beverages, and tobacco products should not be carried, stored, or consumed where this material is in use. Before eating, drinking, or smoking, wash face and hands thoroughly with soap and water.

Exposure Limit(s)

The below constituents are the only constituents of the product which have a PEL, TLV or other recommended exposure limit. At this time, the other constituents have no known exposure limits.

Not applicable

Not applicable Not applicable

Not applicable

Not applicable

Not applicable

7803-51-2	Phosphine	
OSHA	(PEL):	0.3 ppm (TWA)
		0.4 mg/m ³ (TWA)
ACGIH	(TLV):	1 ppm (STEL)
		0.3 ppm (TWA)
Other \	/alue:	Not established

9. PHYSICAL AND CHEMICAL PROPERTIES

Color:	colorless	
Appearance:	gas	
Odor:	garlic	
Boiling Point:	-87 °C -125 °F	
Melting Point:	-133 °C -208 °F	
Vapor Pressure:	502psig @ 20 °C	
Specific Gravity/Density:	Not applicable	
Vapor Density:	1.146(air = 1) @ 20 °C	
Percent Volatile (% by wt.):	100	
pH:	Not applicable	
Saturation In Air (% By Vol.):	Not applicable	
Evaporation Rate:	Not applicable	
Solubility In Water:	27cc gas/100 ml @ 20 °C	
Volatile Organic Content:	Not available	
Flash Point:	(Pyrophoric)	
Flammability (solid, gas):	Not available	
Flammable Limits (% By Vol):	Lower: 1.8	
Autoignition (Self) Temperature:	38 °C 100 °F	
Decomposition Temperature:	Not available	
Partition coefficient (n-	Not applicable	
octanol/water):		
Odor Threshold:	Not available	
Viscosity (Kinematic):	Not applicable	
DUST HAZARD INFORMATION		
Particle Size (microns):	Not ap	plicable
Kst (bar-m/sec):	Not ap	plicable

Particle Size (microns):Kst (bar-m/sec):Maximum Explosion Pressure (Pmax):Dust Class:Minimum Ignition Energy (MIE) (mJ):Minimum Ignition Temperature (MIT) (°C):Minimum Explosive Concentration (MEC) (g/m³):Limiting Oxygen Concentration (LOC) (%):

10. STABILITY AND REACTIVITY

Stability:	Stable
Conditions To Avoid:	None known
Polymerization:	Will not occur
Conditions To Avoid:	None known
Materials To Avoid:	Air, oxidizing agents. Dimethylsulfoxide
Hazardous Decomposition Products:	oxides of phosphorus

11. TOXICOLOGICAL INFORMATION

PRODUCT TOXICITY INFORMATION

Likely Routes of Exposure: Skin, Eyes, Respiratory System.

ACUTE TOXICITY DATA oral (gavage)	rat	Acute LD50	Not an expected route of exposure
dermal	rabbit	Acute LD50	Not an expected route of exposure
inhalation inhalation	rat rat	Acute LC50 4 hr Acute LC50 4 hr	0.079 mg/l 57 ppm
LOCAL EFFECTS ON SKIN AND EYE Acute Irritation Acute Irritation	skin eye	Thermal burn (pyrophoric) Thermal burn (pyrophoric)	
ALLERGIC SENSITIZATION Sensitization Sensitization	skin respiratory	No data No data	
GENOTOXICITY			
Assays for Gene Mutations Ames Salmonella Assay	No data		
OTHER INFORMATION The product toxicity information above has been estimated.			

HAZARDOUS INGREDIENT TOXICITY DATA

Phosphine has a 4-hour inhalation LC50 (rat) value of 57 ppm (0.079 mg/L). Inhalation overexposure is characterized by severe pulmonary irritation, dyspnea, dizziness, lethargy, and stupor. Human evidence indicates that pulmonary irritation and pulmonary edema are the main toxic effects of phosphine inhalation. Phosphine has also been shown to cause central nervous system depression and gastrointestinal irritation, as well as, renal and hepatic toxicity. Acute inhalation overexposure to high concentrations of phosphine can be fatal. This material is pyrophoric and therefore, contact with skin or eyes may produce thermal burns. In an in vivo cytogenetic study, rats exposed to phosphine via inhalation at concentrations of 0, 6.2 and 19 ppm were examined for chromosomal aberrations in whole blood lymphocytes and bone marrow cells. A significant increase in cells with chromosomal aberrations were seen in male rats exposed to 19 ppm phosphine. No increase in cells with chromosomal aberrations were observed in the bone marrow of female rats, nor in the whole blood lymphocytes of male or female rats.

12. ECOLOGICAL INFORMATION

TOXICITY, PERSISTENCE AND DEGRADABILITY, BIOACCUMULATIVE POTENTIAL, MOBILITY IN SOIL, OTHER ADVERSE EFFECTS

The ecological assessment for this material is based on an evaluation of its components.

RESULTS OF PBT AND vPvB ASSESSMENT Not determined

HAZARDOUS INGREDIENT TOXICITY DATA

Component / CAS No.	Toxicity to Algae	Toxicity to Fish	Toxicity to Water Flea
Phosphine 7803-51-2	Not available	Not available	Not available
Hydrogen 1333-74-0	Not available	Not available	Not available

13. DISPOSAL CONSIDERATIONS

13. DISPOSAL CONSIDERATIONS

The information on RCRA waste classification and disposal methodology provided below applies only to the product, as supplied. If the material has been altered or contaminated, or it has exceeded its recommended shelf life, the guidance may be inapplicable. Hazardous waste classification under federal regulations (40 CFR Part 261 et seq) is dependent upon whether a material is a RCRA "listed hazardous waste" or has any of the four RCRA "hazardous waste characteristics." Refer to 40 CFR Part 261.33 to determine if a given material to be disposed of is a RCRA "listed hazardous waste"; information contained in Section 15 of this MSDS is not intended to indicate if the product is a "listed hazardous waste." RCRA Hazardous Waste Characteristics: There are four characteristics defined in 40 CFR Section 261.21-61.24: Ignitability, Corrosivity, Reactivity, and Toxicity. To determine Ignitability, see Section 9 of this MSDS (flash point). For Corrosivity, see Sections 9 and 14 (pH and DOT corrosivity). For Reactivity, see Section 10 (incompatible materials). For Toxicity, see Section 3 (composition). Federal regulations are subject to change. State and local requirements, which may differ from or be more stringent than the federal regulations, may also apply to the classification of the material if it is to be disposed. The Company encourages the recycle, recovery and reuse of materials, where permitted, as an alternate to disposal as a waste. The Company recommends that organic materials classified as RCRA hazardous wastes be disposed of by thermal treatment or incineration at EPA approved facilities. The Company has provided the foregoing for information only; the person generating the waste is responsible for determining the waste classification and disposal method.

14. TRANSPORT INFORMATION

This section provides basic shipping classification information. Refer to appropriate transportation regulations for specific requirements.

US DOT

Dangerous Goods? X Proper Shipping Name Hazard Class: 2.3 Subsidiary Class: 2.1 UN/ID Number: UN219 Inhalation Hazard: Toy Transport Label Requir	9 sic Inhalation Hazard - Zone A
Component / CAS No. Phosphine	Hazardous Substances / Reportable Quantity of Product (lbs) 101.0101
Comments:	Hazardous Substances/Reportable Quantities - DOT requirements specific to Hazardous Substances only apply if the quantity in one package equals or exceeds the product reportable quantity.
TRANSPORT CANADA	
Dangerous Goods? X	

Dangerous Goods? X Proper Shipping Name: Phosphine Hazard Class: 2.3 Subsidiary Class: 2.1 UN Number: UN2199 Transport Label Required: Toxic Gas Flammable Gas

ICAO / IATA

Dangerous Goods? Forbidden

IMO

Dangerous Goods? X Proper Shipping Name: Phosphine Hazard Class: 2.3 Subsidiary Class: 2.1 UN Number: UN2199 Transport Label Required: To

Toxic Gas Flammable Gas

15. REGULATORY INFORMATION

Inventory Information

United States (USA): All components of this product are included on the TSCA Chemical Inventory or are not required to be listed on the TSCA Chemical Inventory.

Canada: All components of this product are included on the Domestic Substances List (DSL) or are not required to be listed on the DSL.

European Economic Area (including EU): When purchased from a Cytec legal entity based in the EU, this product is compliant with the registration of the REACH Regulation (EC) No. 1907/2006 as all its components are either excluded, exempt, pre-registered and/or registered.

Australia: All components of this product are included in the Australian Inventory of Chemical Substances (AICS) or are not required to be listed on AICS. Not to be available except to authorized or licensed persons. APVMA Approval: File Number 51209.

China: All components of this product are included on the Chinese inventory or are not required to be listed on the Chinese inventory.

Japan: All components of this product are included on the Japanese (ENCS) inventory or are not required to be listed on the Japanese inventory.

Korea: All components of this product are included on the Korean (ECL) inventory or are not required to be listed on the Korean inventory.

Philippines: All components of this product are included on the Philippine (PICCS) inventory or are not required to be listed on the Philippine inventory.

OTHER ENVIRONMENTAL INFORMATION

The following components of this product may be subject to reporting requirements pursuant to Section 313 of CERCLA (40 CFR 372), Section 12(b) of TSCA, or may be subject to release reporting requirements (40 CFR 307, 40 CFR 311, etc.) See Section 13 for information on waste classification and waste disposal of this product.

Component / CAS No.	%	TPQ (lbs)	RQ(lbs)	S313	TSCA 12B
Phosphine	97 - 99	500	100	Yes	No
7803-51-2					

FIFRA INFORMATION

This chemical is a pesticide product registered by the United States Environmental Protection Agency (EPA) and is subject to certain labeling requirements under federal pesticide law. These requirements differ from the classification criteria and hazard information required for safety data sheets (SDS), and for workplace labels of non-pesticide chemicals. The hazard information required on the pesticide label is reproduced below. The pesticide label also includes other important information, including directions for use.

EPA Registration Number: 68387-8

DANGER - POISON (Skull and crossbones)

Restricted Use Pesticide (due to high acute inhalation toxicity of phosphine gas)

KEEP OUT OF REACH OF CHILDREN

Fatal if inhaled. The liquid may cause burns. This product is highly toxic to fish and wildlife. Phosphine gas may deaden the sense of smell. Phosphine may ignite spontaneously at levels above its lower flammability limit of 1.8% v/v (18,000 ppm). Ignition of high concentration of phosphine can produce an explosive reaction.

PRODUCT HAZARD CLASSIFICATION UNDER SECTION 311 OF SARA

- Acute
- Fire
- · Reactivity

16. OTHER INFORMATION

NFPA Hazard Rating (National Fire Protection Association)

Health: 4 - Materials that, under emergency conditions, can be lethal.

Fire: 4 - Materials which will rapidly or completely vaporize at atmospheric pressure and normal ambient temperature, or that are readily dispersed in air and which will burn readily.

15

Instability: 2 - Materials that readily undergo violent chemical change at elevated temperatures and pressures.

Reasons For Issue:	Revised Section
Date Prepared:	05/23/2016
Date of last significant revision:	05/23/2016

Component Hazard Phrases

Phosphine

- H220 Extremely flammable gas.
- H314 Causes severe skin burns and eye damage.
- H330 Fatal if inhaled.
- H400 Very toxic to aquatic life.

Hydrogen

H220 - Extremely flammable gas.

Prepared By: Legal & Compliance Services; E-mail: custinfo@cytec.com

This information is given without any warranty or representation. We do not assume any legal responsibility for same, nor do we give permission, inducement, or recommendation to practice any patented invention without a license. It is offered solely for your consideration, investigation, and verification. Before using any product, read its label.